Product Specifications



SSH-12

SnapStak® Hanger for 1/2 in coaxial cable

Dimensions

Nominal Size	1/2 in
Compatible Diameter, maximum	16.256 mm | 0.640 in
Compatible Diameter, minimum	13.716 mm | 0.540 in
Height	41.00 mm | 1.61 in
Length	66.00 mm | 2.60 in
Width	22.80 mm | 0.90 in

Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

General Specifications

Hanger Type	Snap-in hanger
Cables per Hanger	1
Color	Silver
Material Type	Stainless steel
Maximum Stack Height	3
Ordering Note	CommScope® standard product in Asia Pacific | CommScope® standard product in the United States and Canada
Package Quantity	10

Mechanical Specifications

Corrosion Resistance, minimum with no degredation	=500 hours in salt spray chamber
Mounting	3/4 in drilled cable ladder
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Vibration Survival	=4 hours at resonant frequency
Environmental Strength Capability	Double cable weight

Packed Dimensions

Height	15.2 cm | 6.0 in
Length	9.0 cm | 3.5 in
Shipping Weight	0.36 kg | 0.79 lb
Width	10.4 cm | 4.1 in

©2017 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: May 19, 2017

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

©2017 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: May 19, 2017