



WPS-4A

Weather Protection System: 7-16 DIN 1/2" Annular Connections



[Installation instructions](#)



[WPS cross-reference chart](#)



Contact technical support:

1-888-201-6073

techsupport@jmawireless.com

General	Specification	Comment
Cables supported	JMA Wireless JMA12-50, JMA12R-50 Andrew LDF4, LDF4RK, LDF4 RN RFS LCF12, LCF12-50JL NK Draka RFA1200 Leoni Flexline 1/2"R LS/Superior Essex HFC 12D, HFAC 12D Hansen RF5012, RF5012Z Eupen EC4 Rosenberger SL 1/2" R	
Dimensions in. (mm)	3.47 X 1.69 (88.3 x 42.8)	
Weight	0.12 lb 54 g	
Material	Silicone rubber	
Lubricant	Dow Corning Molykote® III	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB- 313 type lamps	
H.A.L.T.	40 hours	
Fire rating	UL94 HB	

03/05/25