PANDUIT™

Infrastructure for a connected world



PLT1M-L1-7 Premium Cable Tie

PLT1M-L1-7

Pan-Ty® locking tie, miniature cross section, 4.0" (102mm) length, nylon 6.6, brown/violet stripe.

Specifications

Material Description	Nylon 6.6 ()
Product Type	Premium Cable Tie
Color	Brown/Violet
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	4
Overall Length (mm)	102
Body Width (In.)	0.1
Body Width (mm)	2.5
Body Thickness (In.)	0.036
Body Thickness (mm)	0.9
Maximum Bundle Diameter (In.)	0.87
Maximum Bundle Diameter (mm)	22.1
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	80
Minimum Loop Tensile Strength (lb)	18
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 1, 11), RoHS Compliant
For Use With	GTS-E, GS2B-E, PTS
Application	General
Part Features	One-piece, all nylon cable tie accommodate a maxinum bundle diamter of 0.82" (21mm).
Label Dimensions (In.)	W x H

RSP Supply Inc. | https://www.rspsupply.com

Packaging Detail

UPC	07498353980
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0043
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.0868