



WPS-DF

Weather Protection System: DIN Female Antenna Port/ Device Seal



[Installation video](#)



[Installation instructions](#)




[WPS cross-reference chart](#)



Contact technical support:
1-888-201-6073
techsupport@jmawireless.com

General	Specification	Comment
Ports supported	Cut to length; see figure below.	
Dimensions in. (mm)	4.00 x 1.41 (101.6 x 35.81)	
Weight	0.13 lb 59.0 g	
Material	Silicone rubber	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 hours	
Fire rating	UL94 HB	



Compatible port dimensions

1

SURFACE SHOULD BE FREE OF FLATS, THREADS, OR RAISED LETTERING WHOSE CHARACTERS ARE TALLER THAN 1/8\"/>

03/05/25