

## K Mounts

3/4" Hole Rooftop Mounts for 800 MHz "Male-Female Contact" Antennas



### STANDARD CONFIGURATION

| Model    | Length of Coax | Coax               | Connector*       |
|----------|----------------|--------------------|------------------|
| K166M    | 17'            | RG-58/U            | Mini-UHF crimped |
| K166T    | 17'            | RG-58/U            | TNC Male crimped |
| KD166T   | 17'            | Pro-Flex™ Plus 195 | TNC Male crimped |
| KE166U   | 17'            | Pro-Flex™ Plus 195 | FME Female       |
| KE166UMT | 17'            | Pro-Flex™ Plus 195 | FME Female**     |



K166

3/8" Snap-In Rooftop Mount for Quarter Wave Antennas (sold in packs of 5 units each)

### STANDARD CONFIGURATION

| Model     | Length of Coax | Coax            | Connector |
|-----------|----------------|-----------------|-----------|
| K44//5PCK | N/A            | Sold Separately | None      |



K44//5PCK

## (B)MBM Series

Black or chrome, 1-1/8"-18 thread; mirror bracket mount

### STANDARD CONFIGURATION

| Model***  | Length of Coax | Coax     | Connector* | Type   |
|-----------|----------------|----------|------------|--------|
| (B)MBM-NC | 17'            | RG-58A/U | None       | N/A    |
| MBMC-NC   | 17'            | RG-58/U  | None       | N/A    |
| (B)MBM    | 17'            | RG-58A/U | PL259      | Solder |
| (B)MBMC   | 17'            | RG-58/U  | TNC        | Crimp  |
| (B)MBMPL  | 17'            | RG-58/U  | Mini-UHF   | Crimp  |



BMBM MOUNTS

For other cable types, lengths or connector configuration options, contact PCTEL Customer Service.

\* Connectors are shipped loose. Connectors may be attached upon request for an additional charge

\*\* Plus MINI-UHF to FME and TNC to FME adapter loose

\*\*\* (B) prefix indicates black option