Finisar FTLF8519P3BTL Datasheet

Finisar FTLF8519P3BTL Duplex SFP 2.67Gbps 500m MMF DDM 850nm

FTLF8519P3BTL Features

- Finisar 1000BASE-SX Ethernet SFP
- Up-to 500m over MMF @ 2.67Gbps
- 850nm Duplex SFP Transceiver
- -40°C - 85°C Operating Case Temperature
- SFF-8724 Digital optical monitoring
- Hot-swappable for SFP LC ports
- Finisar Standard 1 Year Warranty
- Metal enclosure, for lower EMI
- SFP MSA / IEEE Std 802.3
- Finisar FTLF8519P3BTL is RoHS compliant



Applications

- 1000BASE-SX Ethernet
- 1.063/2.125 Gb Fibre Channel

Description

The Finisar FTLF8519P3BTL 1000BASE-SX Ethernet transceiver is a Duplex SFP transceiver for optical communications, rated for distances up to 500m and a maximum bandwidth of 2.67Gbps. The FTLF8519P3BTL transceiver operates at 850nm wavelength. 2Gb/s 850nm FC -40 to 85C SFP Transceiver. Finisar FTLF8519P2xTL Small Form Factor Pluggable (SFP) transceivers are compatible with the Small Form Factor Pluggable Multi-Sourcing Agreement (MSA).

Note: Due to manufacturer restrictions, Finisar FTLF8519P3BTL is a non-cancellable & non-returnable product. Please call to confirm stock. This product is manufactured by Finisar USA, ships directly from Finisar and is covered by full manufacturer warranty within the USA.

About this Data Sheet

This data sheet has been compiled by SanSpot as a service to its clients and is based on publicly available information from the manufacturer at the time of this publication. For most up-to-date information, please visit manufacturer website. SanSpot is not responsible for omissions or typographical errors.