FJ-2SM-015-10M

Ruggedized, Bend Insensitive Singlemode Fiber, DLC to DLC Fiber Distribution Cable, 10 m

Product Classification

Portfolio	CommScope®
Product Series	FJ
Product Type	Wireless Fiber Cable Assemblies
Regional Availability	Asia | Australia/New Zealand | EMEA | Latin America | North America

Construction Materials

Fiber Type	G.657.A2
Total Fibers, quantity	2
Jacket Color	Black

Dimensions

Cord Length	10.00 m | 32.81 ft
Cable Weight	24.9 lb/kft | 37.1 kg/km
Diameter Over Jacket	6.00 mm | 0.24 in

Environmental Specifications

Environmental Space	Indoor | Outdoor
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Construction Type	Direct fiber tail
Interface Body Style, connector A	Straight
Interface Body Style, connector B	Straight
Interface, connector A	DLC
Interface, connector B	DLC
Minimum Bend Radius, furcation	30.0 mm | 1.2 in
Ordering Note	CommScope® non-standard product

Optical Performance

Assembly Insertion Loss, typical	0.50 dB
Assembly Insertion Loss, typical note	Insertion loss is measured at 1310 and 1550 nm

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant

©2019 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 12, 2019

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

* Footnotes

Assembly Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)

©2019 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: February 12, 2019