Bells & Ringers

Bells



Loud Extension Bell

PREMIER® Bells

Loud ringing bells have a non-magnetic aluminum housing that protects two 6-inch gongs from all types of weather and environments. A mounting bracket is attached.

• Hard-wired telephone connections

PREMIER

Item No.	Mfg. Part No.	Description	Voltage Range	Frequency Range	Dimensions
4810317501	PT-101	Loud Extension Bell 95 dB 5900 Ohm Black	55 - 130 VAC	17 - 33 Hz	12.4"L x 5.4"W x 7.5"H
4810327501	PT-102	Loud Extension Bell 95 dB 1000/2650 Ohm Black	55 - 130 VAC	17 - 33 Hz	12.4"L x 5.4"W x 7.5"H



Loud Ringing Bell

PREMIER Bells

Loud ringing bells are constructed with a highly durable plastic housing for indoor or outdoor use. It operates on telephone ringing voltage. This bell can be mounted on most flat surfaces. A water-tight plastic cover protects the ringer mechanism.

• Hard-wired telephone connections

PREMIER

Item No.	Mfg. Part No.	Description	Voltage Range	Frequency Range	Dimensions
4812417501	PT-75BA	Loud Ringing Bell 95 dB 1000/2650 Ohm Black	55 - 130 VAC	17 - 33 Hz	9.8"L x 5.2"W x 5.3"H
4812017501	PT-75BAR	Replacement Ringer Coil Assembly For PT-75BA Bell	55 - 130 VAC	17 - 33 Hz	9.8"L x 5.2"W x 5.3"H

Ringers



Bell Chime Ringer

PREMIER® Ringers

Bell Chime Ringers can function as a loud clear bell and with the flip of a switch can provide a pleasantly soft chime tone. For easy installation, the ringer is equipped with an external modular connection. The ringer operates off 55 to 130 VAC telephone ringing voltage and contains two 3-inch gongs for the chime effect. It provides volume control for the bell and chime, and is equipped with a 7 foot line cord.

• Modular line cord telephone connection

PREMIER

Item No.	Mfg. Part No.	Description	Voltage Range	Frequency Range	Dimensions
4811497501	PT-400	Bell Chime Ringer 75 dB 4600 Ohm With Volume Control And 7 Foot Cord Ivory	55 - 130 VAC	17 - 33 Hz	7.3"L x 5.2"W x 2.5"H



Extension Ringer

PREMIER Ringers

The 139 Extension Ringer is a two-gong, straight line extension ringer, featuring volume control and a double-wound coil for party identification. It is mounted on a steel base with a molded plastic cover.

• Hard-wired telephone connections

PREMIER

Item No.	Mfg. Part No.	Description	Voltage Range	Frequency Range	Dimensions
4812217501	PT-139	Extension Ringer 75 dB With Volume Control Beige	55 - 130 VAC	17 - 33 Hz	5.4"L x 5.2"W x 2.5"H