

Product Specifications

CBC819-DF

Material ID: CBC819-DF

Crossband Coupler, Cellular/PCS



CHARACTERISTICS

Electrical Specifications

3rd Order IMD Test Method	Two +43 dBm carriers
3rd Order IMD, typical	-107 dBm
dc Pass-through	Band 1 Band 2
Isolation Between Paths, minimum	50.0 dB
Lightning Surge Current	15 kA
Lightning Surge Current Waveform	8/20 waveform

Electrical Specifications (Band 1)

Insertion Loss, maximum	0.20 dB
License Band	Cellular
Operating Frequency Band	806 – 940 MHz
Output Power, maximum composite	500 W
Return Loss at Frequency Band, minimum	20 dB @ 806–940 MHz

Electrical Specifications (Band 2)

Insertion Loss, maximum	0.20 dB
License Band	PCS
Operating Frequency Band	1850 – 2000 MHz
Output Power, maximum composite	275 W
Return Loss at Frequency Band, minimum	20 dB @ 1850–2000 MHz

General Specifications

Application	Indoor Outdoor
Includes	Mounting hardware

Product Specifications

CBC819-DF - Material ID: CBC819-DF



Mechanical Specifications

Color	Gray
Connector Interface	7-16 DIN Female
Connector Interface Style	Long neck
Ground Screw Diameter	8.00 mm
Mounting Pipe Diameter	40-160 mm
Mounting Pipe Hardware	Band clamps

Environmental Specifications

Ingress Protection Test Method	IEC 60529:2001, IP68
Operating Temperature	-40 °C to +65 °C (-40 °F to +149 °F)
Relative Humidity	Up to 100%

Dimensions

Depth	50.0 mm 2.0 in
Height	186.0 mm 7.3 in
Volume	1.7 L
Width	186.0 mm 7.3 in
Weight, without mounting hardware	2.0 kg 4.4 lb