No Polish Connectors SC, Single-mode PLUG 900/250 µm 8800

Part Number:
80611326226

The No Polish Connector (NPC) enable fast, on-site installation of kink proof, 1.6 to 3 mm cable with bend insensitive, single mode fiber. The SC PC and SC APC compatible connectors consist of a factory-polished ferrule assembly and a mechanical splice that is installed without installation tools. A screw on boot retains the aramid fiber in the threads and it clamps the cable jacket by squeezing the jacket holder. Both connectors utilize standard, flat cleaves for the splice. Systems integrators and installers for communication companies and private networks will find this connector to be the easiest way to make field terminations that improve the cable management inside buildings or in the outside plant.

Features and Benefits

Field Termination
Right cable length with no cable slack to store

Simple Assembly Tool
Fast, easy installation

250/900 µm connectors and jacketed connectors available
Potentially improve supply chain and inventory management

Factory-Polished fiber stub in ferrule
No on-site polish or adhesives required

No Tool Investment
Enables maximum deployment speed by eliminating the purchase of installation tools and fiber cleavers (Easy Cleaver Combos)



No Polish Connectors SC, Single-mode PLUG 900/250 µm 8800

No Polish Connectors SC, Single-mode PLUG 900/ 250 µm 8800

Specifications

General Specifications	
Product Type	Connectors
Fiber Category	Single-mode (OS2)
Product Type	Connectors

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Environmental Conditions	
Temperature Range, Storage	-40 °C to 85 °C (-40 °F to 185 °F)

Design - Connector	
Connector Type	SC UPC
Housing Color	Blue
Boot Color	White

Optical Specifications - Connector	
Reflectance, Typical	< -40 dB

RoHS COMPLIANT

Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2025 Corning Optical Communications. All rights reserved.