



WPS-DF-T

Weather Protection System: DIN Female Antenna Port/ Device Seal



[Installation instructions](#)



[WPS cross-reference chart](#)



Contact technical support:


1-888-201-6073

techsupport@jmawireless.com

General	Specification	Comment
Ports supported	See figure below.	
Dimensions in. (mm)	1.50 x .38 (38.10 x 9.65)	
Weight	0.05 lb 22.8 g	
Material	Silicone rubber, tri-metal plated brass	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 hours	
Fire rating	UL94 HB	

WPS-DF-T COMPATIBLE PORT SPECIFICATION



1 THREADS MUST BE CONTINUOUS, NO FLATS ALLOWED.

03/05/25