


Subscriber Line Protector, Single Stage

CATALOG NUMBER

SLP10K1F



CERTIFICATIONS



FEATURES

Single stage protection with primary or combination primary/secondary protectors

10 pair protector

Simple installation into Krone® LSA disconnect block

Data Line Terminator (DLT) available where screw terminal connections are required

PRODUCT ATTRIBUTES

Max Continuous Operating Voltage (Uc): 190 VDC

Max Discharge Current (Imax), L+L-PE: 20kA 8/20 µs

Rated Load Current (IL): 1000A

Frequency: 12 Hz Max

Transmission Rate: 8Mbit/s

Protection Modes: L-L

Technology: Single-stage

Connection Type: Krone® LSA-PLUS

Impedance Balance: 48 dB Max

Insertion Loss: .75 Db Max

Return Loss: 22 dB Max

Loop Resistance: 0.2 Ω

Temperature: -4 to 140 °F

Enclosure Material: UL® 94V-0 Thermoplastic

Depth (D): 0.83"


Height (H): 1.36"

Width (W): 4.92"

Unit Weight: 0.05 lb

Certification Details: UL® 497

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical

Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE