# YH292CWC, Cu Compression H Tap and Cover, 250 kcmil-2 AWG Run, 2-14 AWG Tap

By Burndy
Catalog # YH292CWC



Copper Compression H Tap, Tin Plated, Accommoding the following wire sizes - Run (Main): 250 kcmil-2 AWG Class B,C, 4/0 AWG-2 AWG Class I, DLO; Tap 1: 2 AWG-6 AWG Class B, C, Solid, and 2 AWG-8 AWG Class I, DLO. See sale drawing for metric wire size accommodates

## Application

Wire Tap

## General

| | |
|---|---|
| Catalog Number | YH292CWC |
| Color Code | Purple |
| Connector Type | H-TAP W/BLK COVER |
| Die Index | 654 |
| EU RoHS Indicator | Yes |
| Finish Type | Tin-Plated |
| Material | COPPER |
| Plated | Y |
| Plating Type | Tin - Electro Plated |
| Sub Brand | CRIMPIT |
| Temperature Rating | 194 |
| Trade Name | CRIMPIT™ |
| Type | Compression Taps |
| UPC | 781810000298 |
| UPC 12 Digit | 7818100002988 |

## Dimensions

| | |
|---|---|
| Dimension - L Length Overall mm | 23 mm |
| Dimension - Length Overall inch | 0.90 in |
| Dimension - Strip Length inch | 1-1/16 |
| Dimension - Width inch | 1.52 in |

## Electrical Ratings

| | |
|---|---|
| Voltage - Maximum | 35000 |
| Voltage Rating | 35 kV |

## Conductor Related

| | |
|---|---|
| Conductor - Copper Flex G Run | 2;1;1/0;2/0;3/0;4/0 |
| Conductor - Copper Flex G Tap | 8;7;6;5;4;3;2 |
| Conductor - Copper Flex H Tap | 8;7;6;5;4;3;2 |
| Conductor - Copper Flex I Run | 4/0 AWG-2 AWG |
| Conductor - Copper Flex I Tap | 8;7;6;5;4;3;2 |
| Conductor - Copper Flex I Tap Range | 2 AWG-8 AWG |
| Conductor - Copper Flex K Run | 2;1;1/0;2/0;3/0;4/0 |
| Conductor - Copper Flex K Tap | 8;7;6;5;4;3;2 |
| Conductor - Copper Flex M Run | 2;1;1/0;2/0;3/0;4/0 |
| Conductor - Copper Flex M Tap | 8;7;6;5;4;3;2 |
| Conductor - Copper Solid Tap | 6;5;4;3;2 |
| Conductor - Copper Str Run | 2;1;1/0;2/0;3/0;4/0;250 |
| Conductor - Copper Str Run Range | 250 KCMIL-2 AWG |
| Conductor - Copper Str Tap Range | 2 AWG-6 AWG |
| Conductor - Material | COPPER |
| Conductor Type | CODE/FLEX |

## Certifications And Compliance

| | |
|---|---|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL 486A-486B |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

## Logistics

| | |
|---|---|
| Carton Quantity | 25 |
| Minimum Pack Quantity | 1 |
| Pallet Quantity | 2250 |

## Product Assets

3D Models - YH292CWC_MODEL-IGES
3D Models - YH292CWC_MODEL-PDF

3D Models - YH292CWC_MODEL-STEP
Catalogs - Full Line BURNDY Catalog
Catalogs - Section C - Compression Connections
Customer Notices - Prop 65 Notice
Sales Drawings - SD..206566-01



©2024 Hubbell Incorporated. All rights reserved.