Presslok™ Splice Connectors UY2, Cartridge

Part Number:
UY2-CART

With the Presslok™ series of tools and connectors, service providers can meet the demand for enhanced customer services such as high-speed internet, video-on-demand, and video conferencing. Presslok connectors also offer full wire-range capability, increased port size to accommodate up to 2.08 mm (0.082 in) insulation sizes, and solvent resistant plastic construction. As new technologies migrate into the local loop, the importance of reliable connections in the embedded plant has increased exponentially. Each connection is a potential point of failure in high-bandwidth applications, which could require additional time and expense for a technician to repair. That is where the full line of Presslok connectors can really make a difference.

Features and Benefits

Fast installation

Ease of Use

Wide Range of Common Wire Guages

Factory-installed sealant

Dry versions available for Central Offices and Vaults



Presslok™ Splice Connectors, UY2 Gel-filled IDC Butt Splice Connector, Cartridge Packaging (120 pce)

Presslok™ Splice Connectors UY2, Cartridge

Specifications

Design	
Composition	Gel-filled
No. of connections	Two (2)
Connector type	Butt
Conductor	AWG 26 - 19
Conductor Range	0.4 mm to 0.9 mm

General Specifications	
Product type	Copper Splice Connector

Ordering Information	
Product Number	UY2-CART
EAN Code	4059496712658
Packaging method	Cartridge
Units per delivery	1200/1

RoHS COMPLIANT

Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.