



WPS-5

Weather Protection System: 7/8" Connections



[Installation video](#)



[Installation instructions](#)



[WPS cross-reference chart](#)



Contact technical support:

1-888-201-6073

techsupport@jmawireless.com

General	Specification	Comment
Cables supported	Andrew AVA5, AVA5RK, AL5, LDF5, VXL5 RFS LCF78, LCF78-50JL, UCF78 Eupen EC5 NK Draka RFA78 LEONI Flexline 7/8" R LS/Superior Essex LHF 22D, LHF-22DU Hansen RF5078 Rosenberger SL 7/8" Hengxin HCTAY-50-22	
Dimensions in. (mm)	3.90 x 2.00 (99.0 x 50.8)	
Weight	0.16 lb 73 g	
Material	Silicone rubber	
Lubricant	Dow Corning Molykote® III	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Operating temperature	-40 °C to +65 °C (-40 °F to 149 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 hours	
Fire rating	UL94 HB	

01/06/26