BURNDY

Compression Splice Reducer

By Burndy
Catalog # YSR3934FXLTCKITC



CU Splice Reducer, Barrel A 750 kcmil, Barrel B 350 kcmil G,H,I,K,M,373 DLO, Standard Barrel, Internal Chamfer, Tin Plated, Connector is UL/CSA, 90°C Up to 35kV, Kit comes with Clear Heat Shrink, Black/Blue Color Code, 24/19 or L80 Die Index.

Application

Wire Reducing Splice

General

Color Code	Black, Blue
Color Code - Side A	Black
Color Code - Side B	Blue
Connector Type	STANDARD BARREL KITS
Construction Material - Main	Copper
Die Index	24/19
Die Index - Element A	24
Die Index - Element B	19;L80
Die Index Run Side	24
Die Index Tap Side	19;L80
EU RoHS Indicator	Contact Manufacturer
Feature - Barrel Style	Skived
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	HYREDUCER
Temperature Rating	194
Trade Name	HYREDUCER™
Type	YSR-TC
UPC	781810472309
UPC 12 Digit	7818104723099

Dimensions

Dimension - B Length fraction	1-3/4 in
Dimension - B Length inch	1.78 in
Dimension - L Length Overall mm	104 mm
Dimension - Length BB inch	1.69 in
Dimension - Length Overall inch	4.09 in
Dimension - Strip Length inch	1.67 in

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper Flex G Size B	350 kcmil
Conductor - Copper Flex G Size B Range	350 kcmil
Conductor - Copper Flex G Tap	350 KCMIL
Conductor - Copper Flex H Size B	350 kcmil
Conductor - Copper Flex H Size B Range	350 kcmil
Conductor - Copper Flex H Tap	350 KCMIL
Conductor - Copper Flex I Size B	350 kcmil
Conductor - Copper Flex I Size B Range	350 kcmil
Conductor - Copper Flex I Tap	350 KCMIL
Conductor - Copper Flex K Size B	350 kcmil
Conductor - Copper Flex K Size B Range	350 kcmil
Conductor - Copper Flex K Tap	350 KCMIL
Conductor - Copper Flex M Size B	350 kcmil
Conductor - Copper Flex M Size B Range	350 kcmil
Conductor - Copper Flex M Tap	350 KCMIL
Conductor - Copper Str Size	750 KCMIL-350 KCMIL
Conductor - Copper Str Size A	750 kcmil
Conductor - Copper Str Size A Range	750 kcmil
Conductor - Copper Str Size B	350 kcmil
Conductor - Material	COPPER
Conductor Size	750 KCMIL-350 KCMIL
Conductor Type	CODE/FLEX
Wire Size	750 KCMIL-350 KCMIL

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM

UL Listed	No

Logistics

Carton Quantity	6
Minimum Pack Quantity	1
Pallet Quantity	864

Product Assets

3D Models - YSR3934FXLTCKITC_MODEL-IGES
3D Models - YSR3934FXLTCKITC_MODEL-PDF
3D Models - YSR3934FXLTCKITC_MODEL-STEP
Catalogs - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Installation Manuals - SPLICE KIT trilingual
Sales Drawings - 10021428

©2023 Hubbell Incorporated. All rights reserved.