



Heliax® FiberFeed® Bend Insensitive Singlemode Fiber DLC to DLC 48-Fiber Cable Assembly with pulling grip, 150 m

Product Classification

Portfolio	CommScope®
Product Series	RFFT
Product Type	Wireless Fiber Cable Assemblies
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Construction Materials

Fiber Type	G.657.A2
Total Fibers, quantity	48
Jacket Color	Black

Dimensions

Cord Length	150.00 m 492.13 ft
Cable Weight	91.0 kg/km
Diameter Over Jacket	10.28 mm 0.40 in

Environmental Specifications

Environmental Space	Indoor
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Construction Type	Discrete fiber trunk
Interface Body Style, connector A	Straight
Interface Body Style, connector B	Straight
Interface Feature, connector A	Uniboot
Interface Feature, connector B	Uniboot
Interface, connector A	DLC
Interface, connector B	DLC
Minimum Bend Radius	10.3 cm 4.0 in
Minimum Bend Radius, furcation	30.0 mm 1.2 in
Ordering Note	CommScope® non-standard product

Optical Performance

Assembly Insertion Loss, typical 0.50 dB

Assembly Insertion Loss, typical note Insertion loss is measured at 1310 and 1550 nm

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

ISO 9001:2015

Classification

Compliant

Designed, manufactured and/or distributed under this quality management system



* Footnotes

Assembly Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)