

Specifications



Eaton ISOBAR4ULTRA

Isobar 4-Outlet Surge Protector, 6 ft. Cord with Right-Angle Plug, 3330 Joules, Diagnostic LEDs, Metal Housing

General specifications

PRODUCT NAME	Eaton Tripp Lite series Isobar surge protector
CATALOG NUMBER	ISOBAR4ULTRA
UPC	037332010537
PRODUCT LENGTH/DEPTH	3.5 in
PRODUCT HEIGHT	2.5 in
PRODUCT WIDTH	6 in
PRODUCT WEIGHT	2.4 lb
GLOBAL CATALOG	ISOBAR4ULTRA
PRODUCT TYPE	Surge protector

Product specifications

SAFE THERMAL FUSING	Prevents unsafe conditions during extreme extended over-voltages and catastrophic occurrences
SURGE STYLE	ST - STRIP
SWITCHES	Combination AC circuit breaker & 2 position red illuminated on/off switch
VOLTAGE COMPATIBILITY (VAC)	120
CIRCUIT BREAKER	12
FREQUENCY RATING	50/60 Hz
DIAGNOSTIC LED DETAILS	PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)
EMI / RFI FILTERING	40-80 dB
IMMUNITY	Conforms to IEE 587 / ANSI C62.41
PROTECTION MODES	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
RECEPTACLE COLOR	BLACK
RECOMMENDED ELECTRICAL SERVICE	120V (110-125V)
SLOT OR HOLE MOUNT MEASUREMENT (CENTER TO CENTER)	Distance between horizontal tabs = 131.90 mm; Distance between vertical tabs = 58.17 mm
TRANSFORMER ACCOMMODATION	Transformer Accommodation
UL1449 LET THROUGH RATING	330V
INPUT CORD DETAILS	SJT
INPUT CORD GAUGE (AWG)	14
CORD LENGTH	6 Foot
POWER CORD COLOR	Light Gray
HOUSING COLOR	Gray Light gray
OUTLET SPACING	Distance between horizontal outlets = 39.45mm; Distance between vertical outlets = 39.30mm
OUTLETS MEASUREMENT (CENTER TO CENTER)	Distance between horizontal outlets = 39.45mm; Distance

Resources

BROCHURES	Surge Protector and Power Strip Specification Brochure (English)
MANUALS AND USER GUIDES	Owner's Manual for Isobar Surge Suppressors

	between vertical outlets = 39.30mm
MATERIAL	Metal
INPUT PLUG TYPE	NEMA 5-15P
OUTPUT RECEPTACLES	5-15R
PACKAGE CONTENTS	Owner's manual ISOBAR4ULTRA Isobar 4-Outlet Surge Protector, Metal Housing (4) Outlet safety covers
INPUT NOMINAL VOLTAGE	120 VAC
PRODUCT FEATURES	Metal Case Right-Angle Plug Mounting Holes or Slots UL Certified Automatic Shut-Off Diagnostic LED(s)
PRODUCT HIGHLIGHTS	12A resettable circuit breaker prevents dangerous overloads Network-grade 3330-joule surge protection rating Durable metal housing designed for tough environments 6 ft. AC power cord with right-angle NEMA 5-15P plug 4 NEMA 5-15R outlets in exclusive isolated filter banks
PLUG COLOR	White
AC SUPPRESSION JOULE RATING	3330
AC SUPPRESSION COMPONENTS USED	Metal oxide varistors, toroidal balanced chokes, ferrite rod-core inductors and VHF capacitors.
AC SUPPRESSION RESPONSE TIME	NM = 0 ns. CM = <1 ns
AC SUPPRESSION SURGE CURRENT RATING	85,000 amps (36,000 NM / 49,000 CM)
ISOLATED FILTER BANKS	Yes
MAXIMUM SURGE AMPS	135000

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

