

Bonding & Grounding Straps, Harnesses & Braid

#6 AWG BOND STRAPS

Solid, soft bare copper wire with a 1/4" compression terminal on each end. Standard lengths: 6", 11", and 18". Please see chart on pages G17 and G18 for other ordering options.



Ordering Information

EM-3200-18 – 18", Standard packaging: 20/bd, 200/bx, 33 lb/bx.

EM-3200-11 – 11", Standard packaging: 20/bd, 200/bx, 19 lb/bx.

EM-3200-6 – 6", Standard packaging: 20/bd, 200/bx, 12 lb/bx.

"D" BOND STRAPS

Seven strands, uninsulated stranded wire with a ring terminal on each end. Standard "D" bond straps. Standard lengths: 6", 11", and 18". Please see chart on pages G17 and G18 for other ordering options.



Ordering Information

EM-3418-18 – 18", Standard packaging: 20/bd, 200/bx, 30 lb/bx.

EM-3411-11 – 11", Standard packaging: 20/bd, 200/bx, 19 lb/bx.

EM-3406-6 – 6", Standard packaging: 20/bd, 200/bx, 12 lb/bx.

JOINT PEDESTAL BOND STRAPS

Solid #6 AWG with black insulation, 1" strip at one end, 3/8" inside diameter ring terminal at the other. 29-3/8" long from end of conductor to barrel of crimp connector.



Ordering Information

EM-3205-29.375, Standard packaging: 10/bg, 100/bx, 27 lb/bx.

#4 AWG FLEXIBLE HARNESSES

#4 AWG rope-lay 7 x 85 x 32 bare tinned harnesses, with 1/4" ring terminals on each end. 16" long center to center.



Ordering Information

EM-04-16.25

For Electric Motion Company (EMC) part numbers starting with "EM" please contact EMC customer service at 860-379-8515 or cs110@hubbell.com