CB-12-50



Cable Banding, Bulk, 1/2 in x 50 ft Reel (uses CB-LH-25 Locking Heads - not incl)

Product Classification

Product Type	Banding
Product Brand	PIM-Guard®
Ordering Note	ANDREW® standard product (Global)

General Specifications

Color	Black
Mounting	Angle member | Round member

Dimensions

Width	12.7 mm | 0.5 in
Length	15.24 m | 50 ft
Material Thickness	1.524 mm | 0.06 in

Material Specifications

Material Type	Heat-stabilized weather resistant acetal

Mechanical Specifications

Tensile Force	1,112.055 N | 250 lbf

Environmental Specifications

Installation temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Operating Temperature	-65 °C to +90 °C (-85 °F to +194 °F)

Packaging and Weights

Packaging quantity	1

Regulatory Compliance/Certifications

Agency	Classification

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: March 11, 2026

ANDREW® an Amphenol company

CB-12-50

CHINA-ROHS	Below maximum concentration value
CSA	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: March 11, 2026