

RUNPOTEC®

STRONGEST CABLE PULLING TOOLS

New Products

CB 260 – Cable Box

Single wire roller – set of 4

SPECIAL OFFER



Organised and structured cable unwinding
Quick change of rollers or wires



INSTEAD OF € 396,00

€ **369,-**
plus tax

CB 260 Cable Box – set of 4
RUNPOTEC item no. 10216

RC3 – Inspection camera digital - 15 m



Operating the RC3 inspection camera via wireless LAN (WLAN) and RUNPOCAM-APP (optional)

Camera head with front and side camera including 8 x LED lamps – dimmable – IP67

Compatible with
RUNPOTEC cable pulling systems



INSTEAD OF € 350,00

€ **299,-**
plus tax

RC3 - inspection camera - 15 m
RUNPOTEC item no. 10214

RP5 – RUNPOTEC Polyester Ø 5,5 mm

Cable pulling system for pipe ID* 9–32 mm



Available with and without integrated digital meter counter m/ft




From
€ **140,-**
plus tax

All prices and details for the RP5
in the catalogue on page 26.

* ID = Inner diameter



CB 260 **vertically / horizontally** disconnect and connect



Rubberized feet for a safe and non-slip stand



Cable guide clip



SPECIAL OFFER

CB 260 Cable Box - Single wire roller - **set of 4**

CB 260 Cable Box with carrying handle including roll for single wire, wire or cable

- Organised and structured cable unwinding
- Quick change of rollers or wires
- Simple plug-in System
- Versatile stacking and modular extendable
- Cable guide clip to organize single conductors, wires or cables - removable for changing rolls
- Rubberized feet for a safe and non-slip stand
- Suitable for construction sites

For more information see product videos.

INSTEAD OF € 396,⁰⁰

€ **369,-**


plus tax
CB 260 Cable Box - set of 4
RUNPOTEC Item no. 10216



Change cable bundle:
Open and close the roller
with a twist



Possible sizes - cable bundle /
single wire bundle



Filling volume:

Max. filling height: 80 mm
Max. outer diameter: 254 mm
Min. core diameter: 90 mm

5 + 1 FOR FREE



SPECIAL OFFER

CB 260 Cable Box - Single wire roller - **set of 6**

Box with carrying handle including roll for single wire, wire or cable

- Organised and structured cable unwinding
- Quick change of rollers or wires
- Simple plug-in System
- Versatile stacking and modular extendable

For more information see product videos.

INSTEAD OF € 594,⁰⁰

€ **495,-**

plus tax
CB 260 Cable Box - set of 6
RUNPOTEC Item no. 10217





Integrated digital meter counter - m/ft



Triple twisted special polyester fish tape



INTRODUCTORY PRICE

RP5 - RUNPOTEC Polyester Ø 5,5 mm - 30 m

RP5 - Cable pulling system Ø 5,5 mm - 30 m incl. digital meter counter

- 270 kg total breaking load
- Triple twisted special polyester Ø 5,5 mm
- 2 x RG7 Guiding head incl. swivel Ø 7 mm - at the beginning and end
- Glide back protection
- Robust and shockproof storage box suitable for job sites
- Optimum field of application: pipe inner diameter 9 – 32 mm

For more information see product videos.

INSTEAD OF € 202,00

€ **189,-**

RP5 - 30 m incl. meter counter
RUNPOTEC Item no. 10203



Operating the RC3 inspection camera via **wireless LAN** (WLAN) and **RUNPOCAM-APP** (optional)

Camera head with front and side camera incl. 8 x LED lamps dimmable – IP67

Through RTG Ø 6 mm thread – Connection to RUNPOTEC cable pulling systems

INTRODUCTORY PRICE

RC3 - Inspection camera digital - 15 m

- 5.0" IPS – Colour display, removable monitor module with shockproof rubber cover
- RTG Ø 6 mm thread – connection to RUNPOTEC cable pulling systems
- Full HD – image and video Resolution
- Accessory box (8 pieces)
- Lithium-ion battery (3 hours)
- IP67 protection class – camera head and cable

For more information see product videos.

INSTEAD OF € 350,00

€ **299,-**

RC3 inspection camera digital - 15 m
RUNPOTEC Item no. 10214



PROMOTION DESCRIPTION

XB 500 T (Telescop extension) Cable roller

Universal cable drum winder and unwinder for all types of cables and pipes (conductors, cable rings, cable drums - also damaged drums, conduits, ropes and cable drums). With closed lid Ø 500 mm | Load bearing capacity 800 kg With unfolded brackets Ø 800 mm | Filling height 390 mm Incl. 2 x RUNPOSTICKS 410 mm, XB mandrel and clip system The height-adjustable lid is perfectly designed to secure loose cables, cable rings, pipes or 2 cable rings at the same time. It prevents uncontrolled unwinding.

For more information see product video

INSTEAD OF € 339,00

€ **310,-**

XB 500 T - introductory price
RUNPOTEC Item no. 10187





INTRODUCTORY PRICE

GF3 Glass Fiber Ø 3 mm - 30 m

- GF3 - cable pulling system incl. digital meter counter ft/m,
- Fiber glass rod Ø 3 mm with RG7 - Guiding head with front thread incl. swivel and kink protection
 - 16 piece accessories,
 - Easy service access – just open one screw
 - Automatic guide back protection.
 - Jobsite capable, splash water & dust proof
 - Total breaking load: 130 kg
 - Optimal field of application: pipe inner diameter 9 – 45 mm
- For more information see product videos.

INSTEAD OF € 199,00

€ **169,-**

plus tax

GF3 - 30 m - Introductory price
RUNPOTEC Item no. 10193



GF3



INTRODUCTORY PRICE

GF3 SLIM - Glass Fiber Ø 3 mm - 30 m

- GF3 SLIM - cable pulling system incl. digital meter counter ft/m
- Fiber glass rod Ø 3 mm with RG4.5 - Guiding head with front thread (RTG Ø 3 mm) incl. swivel
 - 14 piece accessories
 - Easy service access – just open one screw
 - Automatic guide back protection
 - Jobsite capable, splash water & dust proof
 - Total breaking load: 100 kg
 - Optimal field of application: pipe inner diameter 5 – 40 mm
- For more information see product videos.

INSTEAD OF € 197,00

€ **167,-**

plus tax

GF3 SLIM - 30 m - Introductory price
RUNPOTEC Item no. 10208



GF3 SLIM



PROMOTION DESCRIPTION

RM35 Cable length measuring device + XB 300 Cable roller

- 1 x RM35 Digital cable length measuring device incl. accessories and system case (incl. 2x mountingplate)
 - 1 x XB 300 Cable roller
- Universal cable drum rewinder and unwinder (also for damaged cable drums), loadable up to 300 kg

For more information see product videos.

INSTEAD OF € 463,40

€ **390,-**

plus tax

RM35 - XB 300 - offer
RUNPOTEC Item no. 11143



RM35



XB 300

NEWS - SPECIAL OFFERS - INFORMATION		
CB260 - Single wire roller - set of 4 set of 6		2
RP5 - RUNPOTEC Polyester Ø 5,5 mm		3
RC3 - Inspection camera - digital XB 500 T - Telescopic extension		4
GF3 - Glass Fiber Ø 3 mm GF3 SLIM - Glass Fiber Ø 3 mm		4
RM35 - Digital cable length measuring device + XB 300 - Cable roller		4
RUNPOSTICKS - Comfort package + Cable pulling loop - thread		66
RP5 - Cable pulling system Ø 5,5 mm + Cable pulling loop - hook		66
GF3 - Glass Fiber Ø 3 mm + RC2 Inspection camera		67
GF4.5 - Fiberglass rod Ø 4,5 mm + RC2 Inspection camera		67
CABLE PULLING SYSTEMS		Pipe diameter
Cable lubricant GEL FOAM SPRAY LIQUID		19
RP5 - Cable pulling system Ø 5,5 mm	ID* Ø 9 – 32 mm	26
RUNPOSTICKS - Standard- and comfort package		29
RP1 Cable pulling rod Ø 4 mm	ID* Ø 9 – 25 mm	25
GF3 Glass Fiber Ø 3 mm - Cable pulling system	ID* Ø 9 – 45 mm	30
GF3 SLIM Glass Fiber Ø 3 mm - Cable pulling system	ID* Ø 5 – 40 mm	32
RT 2008 - Mechanical cable pulling tool	ID* Ø 9 – 32 mm	34
MET4 - Steel fish tape Ø 4 mm	ID* Ø 9 – 32 mm	35
Cable pulling loop - hook (quick connection) RTG 6 thread	Ø 14 – 30 mm	36
Cable pulling grip - hook RTG thread loop	Ø 9 – 100 mm	37
Cable diameters - Summary table - Information page	Ø 9 – 100 mm	39
GF4.5 Fiberglass rod Ø 4,5 mm - Cable pulling system	Ø 30 – 80 mm	40
GF6 Fiberglass rod Ø 6 mm - Cable pulling system	Ø 40 – 100 mm	43
GF7.5 GF9 Fiberglass rod Ø 7,5 / 9 mm - Cable pulling system	Ø 50 – 200 mm	47
GF11 Fiberglass rod Ø 11 mm - Cable pulling system	Ø 80 – 250 mm	50
GF15 Fiberglass rod Ø 15 mm - Cable pulling system	Ø 180 – 450 mm	52
Flexible leading head-set	Ø 50 – 450 mm	46
CW 800 E - Capstan winch for horizontal cable pulling		54
Polyester cable pulling rope - incl. steel reel or drum		56
Cable guide roller		57
Metal spiral - Ø 4 mm Nylon fish tape - Ø 4 mm	ID* Ø 9 – 32 mm	60
INSPECTION SYSTEMS - MEASURING DEVICES - SYSTEM-CASE		
RC3 - Inspection camera - digital		20
RC2 - Inspection camera		22
RM35 - Digital cable length measuring device		6
RM80 - Laser distance meter		59
RUNPOTEC system case		58
CABLE ROLLER SYSTEMS		Loadable up to
CB260 - Single wire roller		8
XB 300 - Cable roller Multifunction mandrel	300 kg	10
XB 500 - Cable roller	800 kg	12
XB 500 T (Telescopic extension) - Cable roller	800 kg	13
XB 500 APR - Adapter plate - Roller XB 500 APF - Adapter plate - Feet	80 kg	14
PRO 530 PRO 670 - Cable drum roller	215 kg	15
AS 900 - Roll-off rails	1700 kg	18
RUNPOLIFTER 4500 SET - Cable drum lifter	4500 kg	16
Drum samples - for RUNPOLIFTER 4500 SET - Information page		17
Cable guide roller	4500 kg	57
PRICE LIST - QUALITY CHECK		
Price list		61
Quality check		67

* ID = Inner diameter

RM35 Digital cable length measuring device**CALIBRATABLE**

Foldable



Jobsite capable:
Splash water & dust proof,
shock- and break-proof

Versatile use with cables,
single conductors, ropes,
pipes of Ø 2 mm – 32 mm

Compatible with all unwinding
systems

Battery life in continuous
operation 100 hrs. (without
backlighting)

RUNPOTEC system case




W-BOX | Sortimo COMPATIBLE

The **RM35** is a digital cable length measuring device with which cables, single wires, ropes, pipes or hoses with a diameter of Ø 2 mm to Ø 32 mm can be measured precisely. It is splash-proof and dust-proof, extremely shock-resistant and therefore ideally suited for the construction site. The RM35 accessories included are stowed away in the RUNPOTEC system case, which is compatible with Sortimo. The strap with clip system makes it easy to connect RM35 to the XB 300 XB 500 or XB 500 T cable roller. If the belt is connected to the anchor pad with a clip system, the RM35 is compatible with all conventional unwinding systems.

Display with extensive application possibilities

- 1 Current counter value (pos./neg.), max. measuring distance 99999,99 m
- 2 Countdown, e.g. for repeated cable cutting or drum residual value determination (initial value 200 m minus unwound length 50 m 1 results in current residual value (150 m) – see actual 3)
- 3 Actual - current remaining value (150 m) from the entered countdown value
- 4 Add current counts (positive/negative) to totals (TOTAL 1/2).
- 5 Cable pull direction display (forward/backward)



Scope of delivery – RM35 including extensive accessories (Item no. 10172, 10184, 11143)

- A RM35 Digital cable length measuring device
- B RUNPOTEC system case with case insert for RM35
- C Mountingplate RM35
- D Mountingplate system case
- E Belt with clip system
- F Connecting pad
- G Multi jaws RM35 – round
- H Guide jaws RM35
- I USB-C charger cable



RM35 Digital cable length measuring device - application - accessories - spare parts


Application examples



RM35 with belt and clip system
connected to GF4.5 fiberglass rod



RM35 with belt and clip system
connected to XB 500



RM35 with RUNPOLIFTER L1600 and
3 x 35 mm² cable

Item		Item no.	Rec. trade price
	RM35 Digital cable length measuring device Incl. accessories: RUNPOTEC system case, multi jaws RM35 – round, belt with clip system, connecting pad, mountingplate system case, mountingplate RM35, guide jaws RM35, USB-C charger cable Introductory price	10172	~~390,90 €~~ 349,00 €
 Description of the calibration	RM35 Digital cable length measuring device, calibrated , incl. test certificate according to module F Incl. accessories see item no. 10172	10184	489,00 €
	Belt with clip system and connecting pad To connect with all conventional rolling systems Belt length 1200 mm + connecting pad (2-part) Belt length 2400 mm + connecting pad (2-part)	20706 20714	34,00 € 39,10 €
 Info: Easy changing with 2,5 mm Allen key	Sliding jaw-set RM35 – 4-part Spare part for RM35	20707	13,40 €
 Example photo: Interior view	RUNPOTEC system case With case insert for RM35	20708	56,00 €
 Example photo: Without RM35 and system case	Mountingplate – system case Attachment for fastening to the RUNPOTEC system case, with click system for RM35	20739	40,20 €
 Example photo without RM35	Mountingplate RM35 For attachment with screws (not included), with click system for RM35, lockable	20849	20,50 €
 Ø 12 mm Ø 18 mm Ø 6 mm Ø 24 mm	Guide jaws RM35 – 4 parts For high-precision measuring results Guide jaws grey (Ø 12 mm / 18 mm) Guide jaws red (Ø 6 mm / 24 mm)	20738	17,50 €
 from Ø 2 mm – Ø 15 mm adjustable	Multi jaws RM35 – round For high-precision measuring results Cable diameter adjustable by turning from Ø 2 mm - 15 mm	20850	22,70 €
 Width from 3 mm – 15 mm adjustable	Multi jaws RM35 – angular For precision measurement results of duplex cable, LED cable, ribbon cable etc. Adjustable by turning. Width from 3 mm – 15 mm	20851	22,70 €

CB 260 Cable Box - Single wire roller



CB 260



Ergonomic carrying handle

Release – to separate the boxes horizontally

Roller in which single wire / wire / cable is stored

Cable guide clip for the single wire, wire or cable

Rubberized feet for a non-slip stand

Release – to separate the boxes vertically

Release - to remove the roll



RM35 Digital cable length measuring device
COMPATIBLE

The **CB 260** Cable Box is a single-core unwinder that has been specially developed for managing single-core wires, wires and cables. A cable unwinding system that is suitable for all single-core laying work and control cabinet assembly. The CB 260 is also suitable for control, box and telephone cables and other types of cables. The boxes can be stacked horizontally and vertically and fixed to one another. The rolls can be easily changed using the push button. A special outlet guide ensures that the cables can be unrolled without tangling.


Quick and easy changing of the roller

Remove the cable guide clip to remove the reel


Pressing the red button unlocks the roller



Changing the cable bundle with one twist



CB 260 Cable Box **vertically** / **horizontally** disconnect and connect



Press red buttons to unlock

Remove the cable guide Clip

Press the release button and pull out the clip



Possible sizes – cable bundle / single wire bundle

Filling volume:

Max. filling height: 80 mm
 Max. outer diameter: 254 mm
 Min. core diameter: 90 mm



Rubberized feet for a safe and non-slip stand



CB 260 Cable Box - accessories - spare parts - special offers

Item		Item no.	Rec. trade price
		CB 260 Cable Box – single wire roller Box with carrying handle including roll for single wire, wire or cable and cable guide clip External dimensions: L 310 mm W 280 mm H 157 mm	10215 99,00 €
		Roller CB 260 External dimensions: Ø 260 mm H 87 mm	21005 41,00 €
		Cable guide clip CB 260 for the execution of single wire, wire or cable, removable	21006 4,50 €
		Wall mount CB 260 to secure or fix CB 260 cable boxes to walls or in vehicles	21008 7,40 €

SPECIAL OFFER4x **CB 260** Cable Box - Single wire roller - **set of 4**INSTEAD OF € 396,⁰⁰

€ **369,-**

plus tax

CB 260 Cable Box – set of 4
RUNPOTEC Item no. 10216**SPECIAL OFFER****5 + 1 FOR FREE**6x **CB 260** Cable Box - Single wire roller - **set of 6**INSTEAD OF € 594,⁰⁰

€ **495,-**

plus tax

CB 260 Cable Box – set of 6
RUNPOTEC Item no. 10217

XB 300 Cable roller



The compact **XB 300** is a universal, device for winding in/out cables on all small- to mid-sized cable drums and particularly well suited for damaged cable drums. The XB 300 scores with its small, light and flat design, has a diameter of Ø 300 mm and can be loaded up to 300 kg. Six rubberised feet ensure a non-slip and secure standing position. The removable mandrel allows cable drums with different hole sizes to be used. Here also the multifunction mandrel can be attached to unwind loose cable bundles or single wires. For trouble-free and efficient working without the tangled cables. (Multifunction mandrel is not included).

Compatible with the Multifunction mandrel




Possible applications



Multifunction mandrel

Can only be used in combination with XB 300 (XB 500, XB 500 T)



The **multifunction mandrel** has been specially developed for the XB 300, XB 500 and XB 500 T cable rolling systems. By attaching it to the stainless steel central mandrel and unfolding the 4 side brackets, loose cable bundles or individual wires can also be rolled. Optimum area of application: rolling of loose cable bundles or individual wires up to a max. height of 294 mm and a max. diameter of 430 mm

Possible applications



XB 300 Cable roller - accessories - spare parts - special offers

Item		Item no.	Rec. trade price
	XB 300 Cable roller Ø 300 mm load bearing capacity 300 kg incl. XB mandrel and lateral clip system (for connection with RM35 Cable length measuring device)	10137	114,40 €
	Multifunction mandrel Can only be used in combination with XB 300, XB 500 and XB 500 T	20696	55,00 €
	XB mandrel for XB 300, XB 500 and XB 500 T	20632	10,30 €



Application examples

OFFER DESCRIPTION

XB 300 + multifunction mandrel-set

INSTEAD OF € 169,40

€ 152,-
plus tax

XB 300 - multifunction mandrel-set - offer
RUNPOTEC item no. 10174



W-BOX® | Sortimo COMPATIBLE

OFFER DESCRIPTION

XB 300 – complete-set incl.
multifunction mandrel + system case

INSTEAD OF € 225,40

€ 195,-
plus tax

XB 300 - complete-set - offer
RUNPOTEC item no. 10170



W-BOX® | Sortimo COMPATIBLE

OFFER DESCRIPTION

RP5 + XB 300 – multi-set incl.
multifunction mandrel + system case

1 x RP5 without meter counter - 30 m, triple twisted,
total breaking load 270 kg

1 x XB 300 - incl. multifunction mandrel

The multifunction mandrel has been specially
developed for the XB 300, XB 500 and
XB 500 T cable rolling systems

INSTEAD OF € 387,40

€ 314,-
plus tax

RP5 - 30 m - XB 300 - multi-set - offer
RUNPOTEC item no. 10171



VIDEO

RP5

XB 500 Cable roller



XB MANDREL
Ø 45 mm, removable
for small drums


Lid height adjustable, removable
and reversible 180°



Possible applications





With clip system for
attaching to the RM35
digital cable length
measuring device



The **XB 500** is a universal cable drum winder and unwinder for all types of cables and pipes (conductors, cable rings, cable drums, conduits, ropes and cable drums). It enables trouble-free and rational working without tangled cables. The XB 500 has a diameter of Ø 500 mm and can be loaded up to 800 kg and is suitable for almost every type of drum, especially for damaged cable drums. 12 rubberised feet ensure a non-slip and stable base. The height-adjustable cover is perfectly designed to secure loose cables, cable rings or pipes in the XB 500, thus preventing uncontrolled cable unwinding.

Possible applications in combination with the RUNPOSTICKS push rod set (XB 500 T, XB 500 and XB 300)



Item		Item no.	Rec. trade price
	XB 500 Cable roller, Ø 500 mm load bearing capacity 800 kg, drum width variable, incl. XB mandrel and lateral clip system (for connection with RM35 Cable length measuring device), the RUNPOSTICKS (item no. 20881) can be retrofitted and stored in the lid	10136	~~255,00 €~~ 234,00 €
 	RUNPOSTICKS red (hard) Ø 7,5 mm, 2 x 410 mm stainless steel, RTG Ø 6 mm thread (Can be stored in the lid of the XB 500 and XB 500 T)	20881	16,00 €
	XB mandrel for XB 500 T, XB 500 and XB 300	20632	10,30 €

XB 500 T (Telescopic extension) Cable roller

XB MANDREL
Ø 45 mm,
removable for
small drums

More filling volume through
telescopic extensions



Possible applications






With clip system for
attaching to the RM35
Digital cable length
measuring device




The compact **XB 500 T** (telescopic extension) is a universal cable drum reel and unwinder for all types of cables and pipes (core cables, cable rings, cable drums, empty pipes, ropes and cable drums). It enables trouble-free and efficient work without tangled cables. The XB 500 T (telescopic extension) can hold up to 800 kg and fits almost every type of drum. Especially suitable for damaged cable drums. The height-adjustable lid can be adjusted up to a filling height of 390 mm, making it perfectly designed to secure loose cables, cable rings or pipes in the XB 500 T. This prevents uncontrolled cable unwinding. The 6 fold-out support extensions can be extended up to Ø 800 mm using the telescopic extensions. The RUNPOSTICKS (2 x 410 mm, Ø 7.5 mm) stored in the lid can be screwed onto the thread of the stainless steel center mandrel and thereby prevent smaller or lighter drums from slipping down. 12 rubberized feet ensure a non-slip and secure stand.

The drum can be prevented from falling by screwing the RUNPOSTICKS push rods onto the XB 500 T, XB 500, XB 300.



The RUNPOSTICKS push rods Ø 7,5 mm, length 410 mm, are stored in the lid




Item		Item no.	Rec. trade price
	XB 500 T (Telescopic extension) Cable roller with a closed lid Ø 500 mm load bearing capacity 800 kg with unfolded brackets Ø 800 mm filling height 390 mm incl. 2x RUNPOSTICKS 410 mm (stored in the lid), XB mandrel and clip system	10187	~~339,00 €~~
		Promotional price	310,00 €

XB 500 APR Adapter plate - Roller

The **XB 500 APR - Adapter plate - Roller** can be connected to the XB 500 or XB 500 T cable roller. Ideal for unwinding and rolling up pipe or cable bundles or cable drums. The adapter plate can be quickly connected using fixing brackets and quick-release levers. Thanks to the 4 transport rollers including a parking brake, the combination can be moved or fixed effortlessly. In this combination, the XB 500 and XB 500 T can hold up to 80 kg.

Connection with XB 500 / XB 500 T



Application example



Item		Item no.	Rec. trade price
	XB 500 APR - Adapter plate - Roller with 4 transport wheels including parking brake for XB 500 and XB 500 T	20401	148,00 €

XB 500 APF Adapter plate - Feet

The **XB 500 APF - Adapter plate - Feet** can be connected to the XB 500 or XB 500 T cable roller. Ideal for unwinding and rolling up pipe or cable bundles or cable drums on steel-laminated concrete ceilings during the construction phase. The adapter plate can be quickly connected using fixing brackets and quick-release levers. The four fold-out feet enable a higher stand (21 cm) on the ceiling to be concreted. In this combination, the XB 500 and XB 500 T can hold up to 80 kg.

Connection with XB 500/XB 500 T



Application example



Item		Item no.	Rec. trade price
	XB 500 APF - Adapter plate - Feet with 4 fold-out feet for XB 500 and XB 500 T	20957	148,00 €

PRO 530 | PRO 670 Cable drum roller

AS 900
Roll-off rails



RM35 Digital cable
length measuring device
● COMPATIBLE



Completely pre-assembled

Extra strong bearings and
welded belt edges

Adjustable support rollers

Compact feet - stable,
non-slip base

Rubberized carrying handles

Light and solid aluminium
die casting and conti-
nuous casting

The cable drum unwinder made of light die-cast aluminum and continuous casting with robust, adjustable support rollers is ideal for the highest loads in daily use. The support rollers with spring core axles can be quickly adapted to different cable drum sizes up to a maximum of Ø 1000 mm by adjusting the spacing to 85, 160, 225, 290, 310 and 335 mm. The closed, maintenance-free drum bearings are equipped with welded belt edges and extra strong ball bearings. Four feet made of high-quality plastic ensure a stable and non-slip stand and protect finished floor coverings. PRO 530 and PRO 670 cable drum unwinders can be retrofitted with castors!

Different cable drum sizes up to
max. Ø 1000 mm



Castors can be
retrofitted



Extra strong bearings and
welded belt edges



Item		Item no.	Rec. trade price
	Cable drum roller pre-assembled, incl. support rollers load bearing capacity 215 kg		
	PRO 530 - max. drum width 530 mm	10134	199,00 €
	PRO 670 - max. drum width 670 mm	10135	230,00 €
	Castors in a 4-part-set 4 pieces with parking brakes PU = 4 x castors incl. mounting screws (M10)	20623	75,00 €
	Support roller 530 for cable drum roller PRO 530 roller length 530 mm	20609	29,90 €
	Support roller 670 for cable drum roller PRO 670 roller length 670 mm	20610	31,90 €

RUNPOLIFTER 4500 SET Cable drum lifter



VIDEO

RUNPOLIFTER 4500 SET



KG 4500



RM35 Digital cable length measuring device
COMPATIBLE



Lifting support left

Lifting support right

Max. height 950 mm

Foldable
Compact – easy transportation
Only 22 kg per lifting support



Drum width up to 1250 mm

Drum Ø up to 1600 mm

4500 KG

The **RUNPOLIFTER 4500** is a foldable cable drum lifter that is capable of lifting drums with a maximum diameter of 1600 mm and a maximum weight of 4500 kg and a max. width of 1250 mm. The two included centring cones each have a quick-fastener. Drums with a central hole up to Ø 115 mm can be fixed.


Scope of delivery:

- 1 x Lifting support right
- 1 x Lifting support left
- 1 x Drum shaft
- 2 x Centring cones



Item		Lifter Sets	Shaft lenght	Item no.	Rec. trade price
	RUNPOLIFTER 4500 SET	Lifter 1150	1150 mm	10162	2688,00 €
	1 x Lifting support right	Lifter 1350	1350 mm	10163	2730,00 €
	1 x Lifting support left	Lifter 1600	1600 mm	10164	2771,00 €
	1 x Drum shaft				
	Drum shaft Ø 54 mm				
	High strength hollow shaft, integrated heavy duty plain bearing, stainless steel security mount, high weight saving				
	Length 1150 mm – 11,00 kg - lifting capacity 4.500 kg			20692	519,00 €
	Length 1350 mm – 12,50 kg - lifting capacity 4.500 kg			20693	562,00 €
	Length 1600 mm – 14,30 kg - lifting capacity 4.500 kg			20694	606,00 €
	Centring cones (2 pieces)				
	with quick-release fastener drum central hole up to Ø 115 mm			10147	139,00 €
	Lifter transport wheels				
	4 wheels including mounting screws (optionally retrofittable)			20711	139,00 €
	Lifting supports – RUNPOLIFTER 4500				
	1 x lifting support right + 1 x lifting support left stainless steel, galvanised steel			10161	2153,00 €

RUNPOLIFTER 4500 SET Cable drum lifter - drum samples



Application examples: Drum shaft lengths for suitable drum widths

Length **1600 mm** for drum width **up to 1250 mm**

Length **1350 mm** for drum width **up to 1000 mm**

Length **1150 mm** for drum width **up to 800 mm**

A drum diameter mm	610	710	810	910	1010	1210	1410	1610	1810
B drum width mm	490	520	520	690	710	890	890	1100	1100
cable diameter mm	Cable lengths in m on a drum								
	6	1113	2024	2755					
CAT5/6/7	7	845	1481	2340					
Coaxial	8	637	1064	1463	2731				
3 x 1,5 mm ²	9	472	892	1152	2202	2866			
3 x 2,5 mm ²	10	386	677	980	1768	2349			
5 x 2,5 mm ²	11	314	564	761	1404	1912			
1 x 25 mm ²	12	253	468	643	1206	1540			
	13	237	385	542	1032	1339	2727		
1 x 35 mm ²	14		364	454	881	1159	2265	2967	
7 x 2,5 mm ²	15		297	430	749	1000	1991	2479	
1 x 50 mm ²	16		239	358	632	860	1756	2205	
5 x 6 mm ²	17		226	294	603	736	1545	1959	
1 x 95 mm ²	18		218	281	505	705	1355	1737	
3 x 16 mm ²	19		172	228	485	599	1184	1535	2722
10 x 2,5 mm ²	20		165	219	402	576	1139	1352	2435
5 x 10 mm ²	21		159	211	387	485	991	1304	2172
4 x 16 mm ²	22		122	167	315	468	856	1145	1931
	23		117	161	304	389	827	999	1869
5 x 16 mm ²	24		113	156	294	377	709	967	1657
1 x 185 mm ²	25		110	151	285	365	688	639	1608
3 x 35 mm ²	26		80	116	226	299	668	814	1419
3 x 50 mm ²	27		78	113	221	290	567	700	1244
1 x 240 mm ²	28		76	109	215	282	551	681	1211
24 x 2,5 mm ²	29		73	106	209	226	462	663	1180
5 x 35 mm ²	30		71	103	162	220	450	564	1028
4 x 50 mm ²	31			76	157	214	438	550	1003
1 x 300 mm ²	32			74	153	209	428	537	866
40 x 2,5 mm ²	33			72	150	204	352	451	846
	34				146	158	344	441	828
3 x 95 mm ²	35				108	154	336	431	707
5 x 50 mm ²	36				105	151	329	422	692
4 x 70 mm ²	37				103	148	265	348	678
3 x 120 mm ²	38					144	259	341	664
	39					107	254	334	560
4 x 95 mm ²	40					105	249	327	549
5 x 70 mm ²	41					102	244	264	539
3 x 150 mm ²	42					100	190	259	529
4 x 120 mm ²	43						187	254	437
	44						183	249	430
	45						180	245	422
5 x 95 mm ²	46						177	240	415
3 x 185 mm ²	47						174	187	408
	48						129	184	330
4 x 120 mm ²	49						127	181	325
5 x 120 mm ²	50						125	178	319
	51						123	175	314
3 x 240 mm ²	52						121	172	310
	53							170	305
4 x 185 mm ²	54							126	230
	55							124	235
	56							122	232
	57							121	228
	58							119	225
5 x 150 mm ²	59							117	222
3 x 240 mm ²	60								219
	61								216



The cable examples shown correspond to the load capacity of the RUNPOLIFTER (less than 4500 kg).
Source: Leading cable dealers. All information are non-binding.

AS 900 Roll-off rails

RM35 Digital cable
length measuring device
COMPATIBLE

The **AS 900** unwinding rails are designed for safe unwinding of heavy cable material and cable drums from 450 mm to 2000 mm diameter. One of the two heavy duty rollers can be positioned in 3 different settings. The stable stainless steel-aluminium construction with high-quality, maintenance-free, ball bearing heavy-duty support rollers ensure a long service life. Easy and quick change of drums due to the unwinding brake. Due to their two-part narrow design they are easy to use in cramped spaces. Especially recommended where different cable types are to be processed side by side within a short time. Since some of the drums are in very poor condition, the recommended working load bearing capacity of 400 kg should not be exceeded.

Roll-off brake function



Possible application



Item	Item no.	Rec. trade price
 	10142	864,00 €

AS 900 Roll-off rails-set, 2 pieces
 Maximum load on the rollers: 1700 kg
 Recommended drum weight: 400 kg
 (depending on the condition of the wooden drum)
 Dimensions: L 900 mm | W 305 mm | H 100 mm
 Weight: 23,03 kg
 stainless steel-aluminium construction


Cable lubricant

Item		Item no.	Rec. trade price
 NON-FLAMMABLE Tip: Ask for the package price (box: 8 pieces)	Cable lubricant GEL 1000 g Non flammable Friction-reducing, improved gliding property, non-corrosive, heat-resistant up to 85°C/185°F, non-stick and non-staining, gentle on skin, biodegradable.	30064	8,90 €
 NON-FLAMMABLE Tip: Ask for the package price (box: 24 pieces)	Cable lubricant GEL 250 g Non flammable Friction-reducing, improved gliding property, non-corrosive, heat-resistant up to 85°C/185°F, non-stick and non-staining, gentle on skin, biodegradable.	30467	4,40 €
 NON-FLAMMABLE Tip: Ask for the package price (box: 12 pieces)	Cable lubricant SPRAY 400 ml Special attachment – spray large areas or open the tube for precise streams. Non flammable Excellent lubrication, non-stick, non-drying, colourless, odourless.	20523	8,20 €
 NON-FLAMMABLE Tip: Ask for the package price (box: 12 pieces)	Cable lubricant FOAM 400 ml Special attachment – spray large areas or open the tube for precise streams. Non flammable Excellent lubrication, water-soluble, non-stick, non-drying, VOC-free.	20522	7,10 €
 Tip: Ask for the package price (box: 15 pieces)	Cable lubricant LIQUID 1000 ml Friction-reducing, non-stick and non-staining, colour- and odourless, water soluble	30063	7,40 €

RC3 Inspection camera digital

-  5.0" IPS – Colour display removable monitor module with shockproof rubber rubber cover
-  Accessory box (8 pieces)
-  RTG Ø 6 mm thread – connection to RUNPOTEC cable pulling systems
-  Camera head with front and side camera including 8 x LED lamps – dimmable IP67, Flexible camera cable – 15 m
-  Full HD – image and video resolution
-  Lithium-ion battery (3 hours)
-  IP67 protection class – Camera head and cable

Operate RC3 inspection camera via **wireless LAN (WLAN)** with the APP on your smartphone or tablet (optional)



Flexible double camera system with front and side camera incl. LED lamps – dimmable



Focus distance:
30 mm – 80 mm

Focus distance:
20 mm – 40 mm


RTG Ø 6 mm thread – connection to RUNPOTEC cable pulling Systems

Rotating and holding handle on the backside



* Extensive accessories included

- A** Fiberglass rod Ø 3 mm, 1 m
- B** USB charge cable 1,5 m (Plug: USB / USB-C)
- C** Magnet extra strong
- D** Fishing hook, stainless steel
- E** Thread attachment RC 2 / RC 3
- F** Flexible attachment / malleable 120 mm
- G** Connection thread, RTG Ø 6 mm
- H** Micro Memory Card 8 GB



Item		Length	Item no.	Rec. trade price
	RC3 Inspection camera digital with front and side camera, dimmable, IP67 (camera head and cable), battery life approx. 3 hours, incl. accessory box, (8 pieces / *see description)	15 m Promotional price	10214	~~350,00 €~~ 299,00 €

RC3 Inspection camera - application examples - special offers - accessories

Application examples with RUNPOTEC insertion tools with RTG Ø 6 mm thread



Pipe inspection for large pipe Diameters

GF7.5/GF9/GF11



Pipe inspection from Ø 14 mm and more

GF3 / RP1



Protection rating IP67

GF4.5 / GF3



Ventilation and maintenance inspection

GF4.5 / GF6



Cavity wall inspection

RUNPOSTICKS



Shafts and underfloor ducting

RUNPOSTICKS

**SPECIAL OFFER**

1x **GF3** Glass Fiber Ø 3 mm – 30 m,
incl. meter counter, description p. 30
1x **RC3** - Inspection camera with 15 m cable

INSTEAD OF € 539,00

€ **449,-**

plus tax

GF3 - 30 m – RC3 - 15 m – offer
RUNPOTEC item no. 11150

**SPECIAL OFFER**

1x **RUNPOSTICKS** Comfort-package, p. 28
1x **RC3** - Inspection camera with 15 m cable

INSTEAD OF € 489,00

€ **429,-**

plus tax

RUNPOSTICKS – RC3 - 15 m – offer
RUNPOTEC item no. 11149

Item		Length	Item no.	Rec. trade price
	Camera head flexible Ø 3,9 mm - 1 Meter Front camera with 6 x LED integrated - dimmable, IP67	1 m	21000	63,00 €
	Camera head flexible Ø 5,5 mm - 1 Meter with front and side camera, 6 x LED integrated dimmable, IP67, incl. attachments	1 m	21001	49,00 €
	Camera head flexible Ø 8 mm - 1 Meter Triple lens (1 x front camera, 2 x side camera), 8 x LED integrated dimmable, IP67	1 m	21002	73,00 €

RC2 Inspection camera



RC2 Inspection camera – compatible with all RUNPOTEC products with RTG Ø 6 mm thread

Monitor – 3.5" TFT LCD
16 M colors

RC2 Inspection camera in a robust stainless steel head with cable on a spool

Slot – Micro memory card, recording function

RUNPOTEC system case



W-BOX | **Sortimo** COMPATIBLE

RC2 Inspection camera with 6 integrated LEDs (camera probe protection rating IP67), enclosed in robust stainless steel head (Ø 13 mm) with RTG Ø 6 mm inside connecting thread – compatible to all RUNPOTEC products with RTG Ø 6 mm thread. ATTENTION: Compatible only with RUNPOTEC cable pulling systems! Preservation of evidence, storage function photo, video and audio documentation! Battery operation up to 6 hours. Areas of application: Pipe inspections over long distances of up to 50 m. Suitable for pipes with an inner diameter of 14 mm or more, but also for larger pipe cross-sections (ventilation systems, drainage systems, waste water pipes, etc.).

* Extensive accessories included

- A** RG7 - Guiding head with front thread
- B** Systemglider RC2
- C** High-performance 320-lumen rechargeable LED lamp (Rechargeable via USB-C charging socket)
- D** USB / USB-C charging cable 1,5 m
- E** USB EURO power plug 230 V
- F** Micro memory card 8 GB / adapter
- G** Magnet fishing-set
- H** Fishing hook (Stainless steel)
- I** RC2 thread attachment
- J** Attachment flexible / formable 120 mm
- K** Connection thread-set, RTG Ø 6 mm



Item		Length	Item no.	Rec. trade price
	RC 2 Inspection camera with cable on reel and monitor in the RUNPOTEC system case * Included accessories, see above	30 m	10140	566,00 €
		50 m	10141	608,00 €

* ID = Inner diameter

RC2 Inspection camera - application examples - special offers - accessories

Application examples with RUNPOTEC cable pulling systems



Pipe inspection for large pipe diameters



Pipe inspection from Ø 14 mm and more



Protection rating IP67 waterproof



Ventilation inspection and servicing



Cavity wall inspection, locating and capturing



Shafts and underfloor ducting

30m



+

30m

**SPECIAL OFFER**

1 x GF3 Glass Fiber Ø 3 mm – 30 m,
incl. meter counter, description p. 30
1 x RC2 Inspection camera with 30 m cable

INSTEAD OF € 725,00

€ **659,-**
plus tax

RC2 - 30 m - GF3 - 30 m – offer
RUNPOTEC item no. 11146

50m



+

50m

**SPECIAL OFFER**

1 x GF4.5 Fiberglass Ø 4,5 mm – Profi-Set
50 m, incl. steel reel, description p. 40
1 x RC2 Inspection camera with 50 m cable

INSTEAD OF € 923,00

€ **789,-**
plus tax

GF4.5 - 50 m - RC2 - 50 m – offer
RUNPOTEC item no. 11140

Item		Item no.	Rec. trade price
1 	2 	Camera probe RC2, Ø 13 mm, with cable on spool incl. camera reel 1, IP 67, RTG Ø 6 mm 30 m 50 m Camera reel RC2 – empty 2	20560 20559 20608 300,00 € 345,00 € 29,90 €
	Field of view 64° 300.000 Pixel (720 x 576) protection rating IP 67	Endoscope camera probe flexible 0,8 m, Ø 9 mm for RC2 Inspection camera, 4 x LED (dimnable)	20481 69,00 €
	Extra slim Ø 3,9 mm 100.000 Pixel (320 x 240) Field of view 54°, IP 67	Endoscope camera probe flexible 1 m, Ø 3,9 mm for RC2 Inspection camera, 2 x LED (dimnable)	20488 141,00 €

RC2 / RC3 Inspection camera - accessories - spare parts

Item	Item no.	Rec. trade price
  Detail: USB-C charging socket	High-performance rechargeable LED-lamp 320 lumen, USB-C charging socket (incl. Li-ion battery), protection rating IP67 2 x RTG Ø 6 mm thread (1 x vertical and 1 x horizontal)	20485 47,40 €
	Systemglider RC2 / RC3 L 130 mm W 58 mm H 53 mm RTG Ø 6 mm front thread	20606 22,10 €
 	RG7 - Guiding head with front thread incl. swivel, stainless steel, RTG Ø 6 mm thread	20460 29,00 €
	Thread attachment RC2 / RC3 L 101 mm W 16 mm H 19 mm RTG Ø 6 mm front thread	20607 17,00 €
	Micro memory card 8 GB, class 6 incl. adapter and storage case	20483 6,80 €
	Magnet fishing-set 1,5 – 2,9 kg (pipe Ø 16 – 40 mm)	20475 23,70 €
	Connection thread-set Set of 3 (1 x inside, 1 x outside, 1 x blindcap) RTG Ø 6 mm thread	20484 9,60 €
 	Functionglider with RTG Ø 6 mm ① Stainless steel fishing hook with RTG Ø 6 mm ②	20468 20,60 € 20261 7,00 €
 	Attachment flexible / formable Length: 120 mm stainless steel, RTG Ø 6 mm thread	20509 8,00 €
	RUNPOTEC system case with case insert for RC2 Inspection camera	20612 56,00 €

RP1 Cable pulling rod Ø 4 mm

Beginning: RG6 - Guiding head with special eyelet Ø 6 mm, pressed onto strand



Ending: Eyelet Ø 6 mm, RTG Ø 6 mm thread, screwed to strand

RP1 is not suitable for RT 2008!



RP1, special plastic fish tape Ø 4 mm. Special eyelet: 1 x RG6 - Guiding head with special eyelet. Excellent bending and gliding behavior, large eyelet with hole up to 7 x 2.5 mm² cable, perfect fabrication, no hems and high breaking load. Ending: with screwable eyelet with RTG Ø 6 mm thread. Optimal pipe diameters: Tube Ø 13, 16, 20 and 25 mm

Rod	Rec. pipe ID*	Bending radius rod	TBL - ending	Total breaking load - beginning
Ø				
4 mm	Ø 9 - 25 mm	15 mm	170 KG	170 kg

Item		Length	Item no.	Rec. trade price
	RP1 – special plastic fish tape with RG6 - RUNPOGLIDER guiding head Ø 4 mm Total breaking load: 170 Kg	5 m	30027	17,10 €
		10 m	30028	18,40 €
		15 m	30029	22,10 €
		20 m	30030	25,80 €
		25 m	30042	30,50 €
		30 m	30043	35,30 €

ACCESSORIES – useful in combination with RP1

Item		Ø	Item no.	Rec. trade price
	Cable pulling grip with quick-release fastener incl. swivel stainless steel	4 – 6 mm	20272	26,80 €
		6 – 9 mm	20273	29,90 €
		9 – 15 mm	20274	34,00 €
	Eyelet-set Ø 7 mm, stainless steel RTG Ø 6 mm thread, PU = 3 pieces			
		7 mm	20487	9,40 €

* ID = Inner diameter

RP5 RUNPOTEC Polyester Ø 5,5 mm – Cable pulling system

VIDEO



RP5

KG 270

Triple twisted

PATENTED



Integrated digital meter counter – m/ft



RG7 - Guiding head with swivel Ø 7 mm

Glide back protection



Active

Triple twisted special polyester fish tape Ø 5,5 mm

Beginning: RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Ending: RG7 - Guiding head incl. swivel Ø 7 mm, pressed onto strand

Attention!
electric
conductive

Integrated digital meter counter – m/ft




3 years without battery change (with average use)

Virtually break-free even with tightest radii



Very narrow bending radius


Triple twisted special polyester fish tape



R = 15 mm


50 % less friction resistance


Only punctual contact



Total breaking load 270 Kg

Strand + Pressing + Guiding head + eyelet




Rod	Rec. pipe ID*	bending radius	Total breaking load incl. RG7 - RUNPOGLIDER
Ø			
5,5 mm	Ø 9 – 32 mm	15 mm	270 kg

Item		Length	Item no.	Rec. trade price
	RP5 – RUNPOTEC polyester Ø 5,5 mm in plastic box with integrated digital meter counter – m/ft incl. 2 x RG7 - Guiding head incl. swivel triple twisted special plastic fish tape total breaking load 270 kg	20 m	10202	170,00 €
		30 m	10203	~~202,00 €~~
		Introductory price		189,00 €
	RP5 – RUNPOTEC polyester Ø 5,5 mm in plastic box without meter counter incl. 2 x RG7 - Guiding head incl. swivel triple twisted special plastic fish tape total breaking load 270 kg	20 m	10013	140,00 €
		30 m	10014	162,00 €

* ID = Inner diameter

RP5 Cable pulling system - accessories - spare parts - special offers

Item		Item no.	Rec. trade price
	RP5 replacement fish tape Ø 5,5 mm		
	2 x RG7 - Guiding head incl. swivel		
	triple twisted special plastic tape		
	total breaking load 270 kg		
	20 m	20240	110,00 €
	30 m	20241	126,00 €
	40 m	20242	144,00 €
	RUNPOTEC system case with UNIVERSAL case insert	20613	56,00 €
	RP5 – empty box for replacement fish tape RP5 20 m or 30 meter	30146	36,10 €
	Cable pulling grip with quick-release fastener incl. swivel, stainless steel		
	Ø 4 – 6 mm	20272	26,80 €
	Ø 6 – 9 mm	20273	29,90 €
	Ø 9 – 15 mm	20274	34,00 €
	Cable pulling loop with hook (quick-release fastener) – set of 4 Caps outside Ø: 14 17 23 30 mm stainless steel, PU = 4 pieces	10159	42,20 €

Information



Compatible cable pulling grip range see page 38.

30m

**SPECIAL OFFER**

1 x RP5 without meter counter - 30 m

1 x XB 300 with multifunction
mandrel in RUNPOTEC system case, p. 10INSTEAD OF € 387,⁴⁰**314,–**

plus VAT.

RP5 - 30 m – XB 300 – Multiset – offer
RUNPOTEC item no. 10171

30m

60m

Accessories
included in
the storage
compartment**SPECIAL OFFER**

1 x RP5 without meter counter - 30 m

1 x GF4.5 Fiberglass rod Ø 4,5 mm - 60 m,
incl. steel cage, see page 40INSTEAD OF € 503,⁰⁰**411,–**

plus VAT.

RP5 - 30 m – GF4.5 - 60 m – offer
RUNPOTEC item no. 11120

RUNPOSTICKS Push rod system

RC2 / RC3 –
Inspection camera
COMPATIBLE



Item		Item no.	Rec. trade price
	RUNPOSTICKS - Comfort-package (19-parts) 10 x Basalt rods with extreme bending radius, 5 x 1 m red/hard Ø 7,5 mm, 3 x 1 m black/medium Ø 5,5 mm, 2 x 1 m yellow/soft Ø 4,5 mm stainless steel, RTG Ø 6 mm thread 1 x RG7 - Guiding head incl. swivel, 1 x Strong magnet, 1 x connection thread, 1 x Ball chain, 1 x eyelet with ring, 1 x fishing hook, 1 x Special sliding hook, stainless steel 1 x Shockproof LED-lamp incl. 1 x AAA battery 1 x Storage bag with shoulder strap	10020	139,00 €
	RUNPOSTICKS - Standard-package (17-parts) Content: same as RUNPOSTICKS Comfort-package without special sliding hook and shockproof LED-lamp (Description see above)	10016	119,00 €
 	Special sliding hook – Stainless steel overcomes obstacles up to 8 cm, excellent gliding behaviour for all surfaces, with tilt function, extensive mounting options for cable RTG Ø 6 mm thread	30239	20,80 €
 	Functionglider RTG Ø 6 mm thread	20468	20,60 €
	LED-Lamp 130 lumen incl. 1 x AAA battery, shockproof, extra long battery life, RTG Ø 6 mm thread	20059	21,60 €
  Detail: USB-C charging socket	High-performance rechargeable LED-lamp 320 lumen, USB-C charging socket (incl. Li-ion battery), protection rating IP67 2 x RTG Ø 6 mm thread (1 x vertical and 1 x horizontal)	20485	47,40 €

RUNPOSTICKS Push rod system - accessories - spare parts

Item		Item no.	Rec. trade price
		RUNPOSTICKS accessories-set fishing hook, strong magnet, ball chain (steel), connection thread, eyelet with ring	10042 24,70 €
	 Video RG - RUNPOGLIDER guiding head	RG7 - Guiding head with eyelet Ø 7 mm incl. swivel, breaking load: > 270 kg RTG Ø 6 mm thread	20238 29,00 €
		RUNPOSTICKS yellow (soft) Ø 4,5 mm, 2 x 1 m stainless steel, RTG Ø 6 mm thread	10043 19,00 €
		RUNPOSTICKS black (medium) Ø 5,5 mm, 2 x 1 m stainless steel, RTG Ø 6 mm thread	10044 20,00 €
		RUNPOSTICKS red (hard) Ø 7,5 mm, 2 x 1 m stainless steel, RTG Ø 6 mm thread	10045 20,00 €
		Fiberglass rods Ø 3 mm, 2 x 0,45 m stainless steel, RTG Ø 6 mm thread	20457 12,40 €
		Fishing hook stainless steel, RTG Ø 6 mm thread	20261 7,00 €
		Eyelet incl. ring stainless steel, RTG Ø 6 mm thread	30236 5,50 €
		Magnet extra strong holding force 2,5 kg stainless steel, RTG Ø 6 mm thread	20260 9,30 €
		Connection thread stainless steel, RTG Ø 6 mm thread	30210 4,30 €
		Ball chain , length 0.5 m total breaking load: 25 kg stainless steel, RTG Ø 6 mm thread, steel chain	20262 10,30 €
		Pull loop , stainless steel rope RTG Ø 6 mm thread Ø 1,5 mm (loop length 75 mm) Ø 2 mm (loop length 35 mm)	20428 7,10 € 20427 7,10 €
	 Product fish hook set	Fishing hook-set stainless steel, RTG Ø 6 mm thread PU = 4 fishing hook	20614 24,70 €
		Drag rope , length 0.5 m with ball magnet and starting head stainless steel, RTG Ø 6 mm thread	20455 17,50 €
		Storage bage for all accessories, incl. shoulder strap	30009 22,70 €
	 Video cable pulling loop	Cable pulling loop with RTG Ø 6 mm thread – set of 4 cap outside Ø: 14 17 23 30 mm cap inside Ø: 12 15 20 27 mm stainless steel, RTG Ø 6 mm thread, PU = 4 pc	10154 42,20 €

GF3 Glass Fiber Ø 3 mm – Cable pulling system

VIDEO



GF3

KG 130

PATENTED



**KNICKSCHUTZ
KINK PROTECTION**

Automatic glide back protection

Integrated digital meter counter – m/ft



Attention!
electric
conductive

Front end: Guiding head with RTG Ø 6 mm front thread, swivel and kink protection

Rear end: Kink protection with RTG Ø 6 mm inner thread

RC2 / RC3 – Inspection camera

COMPATIBLE


***Accessory box (16-parts)**



Extreme bending radius

Revolutionary kink protection

R = 38 mm





Easy service opening / accessory box

Anti-slip coating

Just open one screw

Accessory box 16-parts



Rod	Rec. pipe ID*	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	Ø 9 – 45 mm	38 mm	28 mm	450 kg	130 kg

Item		Length	Item no.	Rec. trade price
	GF3 Glass Fiber Ø 3 mm with integrated digital meter counter – ft/m 2 x kink protection on fiberglass rod 16-piece accessories (*see content) Box with anti-slip coating	20 m	10192	184,00 €
		30 m	10193	~~199,00 €~~
		Introductory price		169,00 €
		50 m	10195	219,00 €
	GF3 Glass Fiber Ø 3 mm without meter counter 2 x kink protection on fiberglass rod 16-piece accessories (*see content) Box with anti-slip coating	20 m	10196	117,50 €
		30 m	10197	131,00 €
		50 m	10198	156,50 €

* ID = Inner diameter

GF3 – Cable pulling system - accessories - spare parts

Item		Item no.	Rec. trade price
	GF3 Replacement fiberglass rod Ø 3 mm incl. RG7 - Guiding head with front thread and eyelet Ø 7 mm incl. swivel RTG Ø 6 mm thread 20 m 30 m 50 m	20816	46,50 €
		20817	54,60 €
		20818	66,00 €
 	GF3 Repairing-kit Ø 3 mm – 15-parts 1 x RG7 - Guiding head with front thread 2 x Kink protection 1 x Special glue 3 g 2 x Mounting wrench 1 x Eyelet Ø 7 mm 6 x Adhesive joint for Ø 3 mm 1 x Coupling joint for Ø 3 mm 1 x Starting head Ø 11 mm Stainless steel, RTG Ø 6 mm thread	20819	36,80€
 	GF3 Guiding head with kink protection-set Ø 3 mm, stainless steel, RTG Ø 6 mm thread 1 x RG7 - Guiding head with front thread 1 x Kink protection 2 x Mounting wrench 1 x Eyelet Ø 7 mm	20826	30,50 €
	GF3 Adhesive joint-set Ø 3 mm Brass, PU = 6 pieces	20824	6,00 €
 	GF3 Mounting-wrench-set Ø 3 mm stainless steel, PU = 2 pieces	20825	4,20 €
 	Eyelet-set Ø 7 mm stainless steel, RTG Ø 6 mm thread, PU = 3 pieces	20487	9,40 €
 	Pulling eyelet-set Ø 7 mm stainless steel, RTG Ø 6 mm thread, PU = 3 pieces	20411	7,20 €
 	Starting head Ø 11 mm stainless steel, RTG Ø 6 mm thread	20829	4,10 €
	Magnet fishing-set 1,5 – 2,9 kg (tube Ø 16 – 40 mm) 5 kg STRONG (tube Ø 50 –100 mm) RTG Ø 6 mm thread	20475 20476	23,70 € 47,40 €
 	Coupling joint-set GF3 Ø 3 mm stainless steel, PU = 3 pieces	20108	7,20 €
 	Cable pulling grip with thread incl. swivel stainless steel, RTG Ø 6 mm thread Ø 4 – 6 mm Ø 6 – 9 mm Ø 9 – 13 mm	20365 20366 20367	18,50 € 19,60 € 29,90 €
 	Cable pulling loop with RTG 6 thread – set of 4 Protective caps outside Ø: 14 17 23 30 mm stainless steel, RTG Ø 6 mm thread PU = 4 pieces	10154	42,20 €

GF3 SLIM Ø 4.5 mm Glass Fiber Ø 3 mm – Cable pulling system

VIDEO



GF3 SLIM

KG 100

PATENTED



FTTH
FIBER TO THE HOME

SLIM
Ø 4.5 mm

Automatic glide back protection

Integrated digital meter counter - m/ft



Beginning: RG4.5 - Guiding head with front thread (RTG Ø 3 mm) incl. swivel

Ending: Ending joint with RTG Ø 3 mm, stainless steel


Attention!
electric
conductive

***Accessory box (14-parts)**




FTTH - Glass fiber installation

Speedpipe from Ø 5 mm inner diameter



Ideally suited for occupied pipes

RG4.5 Guiding head Ø 4,5 mm




Easy service opening / accessory box

Anti-slip-coating



Just open one screw


Accessory box 14-parts

Rod	Rec. pipe ID*	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
3 mm	Ø 5 – 40 mm	40 mm	28 mm	450 kg	100 kg

Item		Length	Item no.	Rec. trade price
	GF3 SLIM Glass Fiber Ø 3 mm with integrated digital meter counter – ft/m RG4.5 - Guiding head with front thread incl. swivel 14-piece accessories (*see content) Box with anti-slip coating	20 m	10207	182,00 €
		30 m	10208	~~197,00 €~~
		Introduutory price		167,00 €
		50 m	10209	217,00 €
	GF3 SLIM Glass Fiber Ø 3 mm without meter counter RG4.5 - Guiding head with front thread incl. swivel 14-piece accessories (*see content) Box with anti-slip coating	20 m	10210	115,50 €
		30 m	10211	129,00 €
		50 m	10212	154,50 €

* ID = Inner diameter

GF3 SLIM Ø 4.5 mm - Cable pulling system - accessories - spare parts

Item		Item no.	Rec. trade price
	GF3 SLIM Replacement fiberglass rod Ø 3 mm with ending joints, incl. RG4.5 - Guiding head, eyelet and starting head Ø 4,5 mm		
	20 m	20952	35,00 €
	30 m	20953	43,00 €
	50 m	20954	55,00 €
	GF3 SLIM Repairing-kit Ø 3 mm – 8-parts 1 x Special glue 3 g 5 x Ending joint with RTG Ø 3 mm thread 2 x Coupling joint Ø 3 mm	20951	19,90 €
 	GF3 SLIM Ending joint-set stainless steel, RTG Ø 3 mm thread, PU = 5 pieces	20950	10,90 €
 	GF3 SLIM Pulling eyelet-set Ø 4,5 mm stainless steel, RTG Ø 3 mm thread, PU = 3 pieces	20947	7,90 €
 	GF3 SLIM Starting head-set Ø 4,5 mm stainless steel, RTG Ø 3 mm thread, PU = 3 pieces	20948	8,00 €
 	GF3 SLIM Starting head-set Ø 6 mm stainless steel, RTG Ø 3 mm thread, PU = 3 pieces	20949	8,50 €
 	GF3 SLIM Adapter thread-set RTG Ø 3 mm internal thread to RTG Ø 6 mm external thread stainless steel, PU = 3 pieces	20955	9,50 €
Combination options – from RTG Ø 3 mm internal thread to RTG Ø 6 mm external thread			
	With the RC2 Inspection camera head		
	With cable pulling grip – RTG Ø 6 mm thread		
	With cable pulling loop for cable with plug		
	With cable pulling loop for duplex cable		
	With cable pulling loop for single cable		
	GF3 Coupling joint-set Ø 3 mm for GF3 and GF3 SLIM, stainless steel, PU = 3 pieces	20108	7,20 €
 Only Ø 4,5 mm	RG4.5 - Guiding head with front thread (RTG Ø 3 mm) incl. swivel stainless steel, RTG Ø 3 mm thread	20956	22,00 €
	Pulling grip for fiberglass rod Ø 3 – 6 mm	30070	6,40 €
	Special glue 3 g	30050	8,40 €
 NON-FLAMMABLE Tip: Ask for the package price	Cable lubricant SPRAY 400 ml	20523	8,00 €
	Cable lubricant FOAM SPRAY 400 ml (with folding spray tube) Non flammable	20522	7,00 €
	Cable lubricant GEL 1000 g	30064	8,70 €
	Cable lubricant GEL 250 g	30467	4,30 €

RT 2008 Mechanical cable pulling tool



RT 2008

The problem solver for
low pipe cross section
Ø 9 – 32 mm




Attention!
electric
conductive



W-BOX | Sortimo COMPATIBLE

1. Induct



2. Fix



3. Pump



Item		Item no.	Rec. trade price
	RT 2008 - complete-set 1 x RT 2008 1 x RUNPOTEC system case, with RT 2008 case inlay 1 x MET4 metal spiral with RG6 - Guiding head – 15 m Plug-in attachments: 1 x Ø 20 mm, 1 x Ø 25 mm, 1 x Ø 32 mm, 1 x Ø 40 mm, 1 x socket flexible, 2 x plug in coupling, 1 x belt clip	10000	308,00 €
	RT 2008 incl. clamping element	20004	183,00 €
	Set plug in coupling + belt clip	20333	8,20 €
	Plug-in attachment for corrugated pipe outer Ø 20 mm	20020	9,30 €
	Plug-in attachment for corrugated pipe outer Ø 25 mm	20025	9,30 €
	Plug-in attachment for corrugated pipe outer Ø 32 mm	20032	9,30 €
	Plug-in attachment for corrugated pipe outer Ø 40 mm	20040	9,30 €
	Plug-in attachment socket flexible	20010	8,20 €
	Plug-in attachment 90° rigid socket (also for corrugated pipe outer Ø 16 and 20 mm)	20253	17,50 €
	RUNPOTEC system case with RT 2008 case inlay	20611	56,00 €

MET4 Steel fish tape Ø 4 mm

Beginning: RG6 - Guiding head with special eyelet Ø 6 mm, pressed onto strand.



Ending: Eyelet Ø 6 mm, pressed onto strand

Optimal in combination with the revolutionary RT 2008



3 times offset wound metal spiral



Application example / symbol image

MET4, metal spiral Ø 4 mm. Special eyelet: 1 x RG6 - Guiding head with special eyelet. Excellent bending and gliding behavior, large eyelet with hole up to 7 x 2.5 mm² cable, perfect fabrication, no hems and high breaking load. Ending: eyelet Ø 6 mm, pressed onto strand. Optimal pipe diameters: Tube Ø 13, 16, 20, 25 and 32 mm.

Rod	Rec. pipe ID*	Bending radius rod	TBL - ending	Total breaking load - beginning
Ø				
4 mm	Ø 9 - 32 mm	25 mm	170 Kg	170 Kg

Item		Length	Item no.	Rec. trade price
	MET4	5 m	30054	19,60 €
	metal spiral	10 m	30017	26,80 €
	Ø 4 mm	15 m	30018	35,00 €
	Total breaking load:	20 m	30019	43,30 €
	170 Kg	25 m	30020	52,00 €
		30 m	30021	56,00 €
		Lengths up to 50 m possible	30031	Price o. r.

ACCESSORIES – useful in combination with MET4


Item		Ø	Item no.	Rec. trade price
		4 – 6 mm	20272	26,80 €
		6 – 9 mm	20273	29,90 €
		9 – 15 mm	20274	34,00 €
 		Application: Quick-release fastener compatible with RG - RUNPOGLIDER guiding head		

* ID = Inner diameter


CABLE PULLING LOOP with hook (quick connection) / RTG 6 thread

Cable pulling loop with hook or RTG Ø 6 mm thread, with protective cap and flexible loop made of stainless steel with Ø 1.5 mm. Optimal field of application: To pull pre-fabricated cables incl. plugs in a protected manner. For pipes with an inner diameter of 14 mm or more and non-guided lines.


Examples: pulling force transferred to the cable



Use the protective cap to pull the plugs through pipes or other situations in a protected manner. 4 variants for different plug sizes.




Connect: cable pulling loop with hook (compatible with all RUNPOTEC products with RG - guide heads)





Connect: pulling loop with RTG Ø 6 mm thread

Swivel allows the cable to rotate in the tube



Item		Caps inner Ø	Caps outside Ø	Item no.	Rec. trade price
	Cable pulling loop with hook (quick-release fastener) – set of 4 Total breaking load: 100 kg stainless steel PU = 4 pieces	12 mm	14 mm	10159	42,20 €
		15 mm	17 mm		
		20 mm	23 mm		
		27 mm	30 mm		
	Cable pulling loop with hook (quick-release fastener) – individually Total breaking load: 100 kg stainless steel	12 mm	14 mm	20628	14,40 €
		15 mm	17 mm	20629	14,90 €
		20 mm	23 mm	20630	15,50 €
		27 mm	30 mm	20631	16,00 €
	Cable pulling loop with RTG 6 thread – set of 4 Total breaking load: 100 kg stainless steel, RTG Ø 6 mm thread PU = 4 pieces	12 mm	14 mm	10154	42,20 €
		15 mm	17 mm		
		20 mm	23 mm		
		27 mm	30 mm		
	Cable pulling loop with RTG 6 thread – individually Total breaking load: 100 kg stainless steel, RTG Ø 6 mm thread	12 mm	14 mm	20624	14,40 €
		15 mm	17 mm	20625	14,90 €
		20 mm	23 mm	20626	15,50 €
		27 mm	30 mm	20627	16,00 €

CABLE PULLING GRIP with hook (quick connection) / RTG 6 thread / loop





For **cable diameter Ø 4 – 15 mm**. Compatible with RP5, RP1, GF3 / GF4.5 / GF6 Fiberglass rod, RUNPOSTICKS. Made of high quality stainless steel weave. Extremely long service life thanks to new connection technology.

Item		Total breaking load	Weave length	Ø	Item no.	Rec. trade price
Cable pulling grip with quick-release fastener incl. swivel, stainless steel		200 kg	180 mm	Ø 4 – 6 mm	20272	26,80 €
			200 mm	Ø 6 – 9 mm	20273	29,90 €
			350 mm	Ø 9 – 15 mm	20274	34,00 €




For **cable diameter Ø 4 – 13 mm**. Compatible with GF3 / GF3 SLIM (incl. adapter thread) / GF4.5 / GF6 Fiberglass rod and RUNPOSTICKS. Made of high quality stainless steel weave. High-quality materials with a long service life! Advantages of swivel: Cable can rotate in the tube, prevents unintentional unscrewing from the thread.

Item		Total breaking load	Weave length	Ø	Item no.	Rec. trade price
Cable pulling grip with RTG Ø 6 mm thread incl. swivel stainless steel		120 kg	180 mm	Ø 4 – 6 mm	20365	18,50 €
			200 mm	Ø 6 – 9 mm	20366	19,60 €
			300 mm	Ø 9 – 13 mm	20367	29,90 €

For **cable diameter Ø 4 – 13 mm**. Compatible with GF3 / GF3 SLIM / GF4.5 / GF6 Fiberglass rod and RUNPOSTICKS. Made of high quality stainless steel weave. High-quality materials with a long service life! Advantages of swivel: Cable can rotate in the tube, prevents unintentional unscrewing from the thread.

Item		Total breaking load	Weave length	Ø	Item no.	Rec. trade price
Cable pulling grip with loop incl. swivel loop length 100 mm, stainless steel		200 kg	180 mm	Ø 4 – 6 mm	30039	21,60 €
			200 mm	Ø 6 – 9 mm	30040	23,70 €
			300 mm	Ø 9 – 13 mm	30041	36,10 €

CABLE PULLING GRIP with RTG 6 thread / RTG 12 thread / loop - accessories

For **cable diameter Ø 9 – 31 mm**. Compatible with GF3 / GF3 SLIM (incl. adapter thread) / GF4.5 / GF6 / GF7.5 / GF9 / GF11 F fiberglass rod and RUNPOSTICKS. Made of high quality stainless steel weave. High-quality materials with a long service life! Advantages of swivel: Cable can rotate in the tube, prevents unintentional unscrewing from the thread.

Item	Total breaking load	Weave length	Ø	Item no.	Rec. trade price
Cable pulling grip with loop and RTG Ø 6 mm thread incl. swivel stainless steel  Information: Not optimal in combination with CW 800 E Capstan winch	180 kg	350 mm	Ø 9 – 15 mm	20266	41,20 €
		400 mm	Ø 15 – 19 mm	20267	43,30 €
		400 mm	Ø 19 – 25 mm	20268	44,30 €
		450 mm	Ø 25 – 31 mm	20269	46,40 €
Quick-release fastener with RTG Ø 6 mm thread For connecting RUNPOTEC cable pulling grip with RTG Ø 6 mm thread to all RUNPOTEC products with the RG - RUNPOGLIDER guiding head 				20388	22,70 €



For **cable diameter Ø 30 – 100 mm**. Preferably in combination with all fiberglass rods and RUNPOTEC products with RTG Ø 12 mm thread. Made of high quality stainless steel weave. Advantages of swivel: Cable can rotate in the tube, prevents unintentional unscrewing from the thread.

Item	Total breaking load	Weave length	Ø	Item no.	Rec. trade price
Cable pulling grip with loop and RTG Ø 12 mm thread incl. swivel With additional RTG Ø 6 mm thread stainless steel  Information: Not optimal in combination with CW 800 E capstan winch	1000 kg	800 mm	Ø 30 – 40 mm	20436	64,00 €
		900 mm	Ø 40 – 50 mm	20437	68,00 €
		1000 mm	Ø 50 – 60 mm	20438	72,00 €
		1100 mm	Ø 60 – 70 mm	20439	81,00 €
		1200 mm	Ø 70 – 85 mm	20440	96,00 €
		1300 mm	Ø 85 – 100 mm	20441	113,00 €



For **cable diameter Ø 10 – 100 mm**. Preferably combined with CW 800 E Capstan winch. Made of flexible, galvanized steel double weave. In the case of permanent tension, it is recommended to work in combination with the connection swirl with swivel (see accessories item no. 10176).



Item	Total breaking load	Weave length	Ø	Item no.	Rec. trade price
Cable pulling grip with loop Flexible, galvanized steel double weave Long lifetime  ! CW 800 E – capstan winch COMPATIBLE	1019 kg	600 mm	Ø 10 - 15 mm	20661	41,20 €
	2080 kg	600 mm	Ø 15 - 20 mm	20662	43,30 €
	2080 kg	600 mm	Ø 20 - 25 mm	20663	44,30 €
	2080 kg	1000 mm	Ø 25 - 30 mm	20664	48,40 €
	3059 kg	1250 mm	Ø 30 – 40 mm	20665	55,00 €
	4078 kg	1250 mm	Ø 40 – 50 mm	20666	60,00 €
	4996 kg	1500 mm	Ø 50 – 60 mm	20667	70,00 €
	4996 kg	1500 mm	Ø 60 – 70 mm	20668	82,00 €
	4996 kg	1500 mm	Ø 70 – 85 mm	20669	96,00 €
	5812 kg	1500 mm	Ø 85 – 100 mm	20670	109,00 €

ACCESSORIES – Optimal in combination with cable pulling grip, pull rope and CW 800 E Capstan winch

Item	Item no.	Rec. trade price
 Connection swirl with swivel Ø 30 mm L 132 mm, stainless steel	10176	196,00 €

Cabel examples with diameters

Cabel pulling grip

Cable-symbolphoto	Cable Ø	Cable section	Cable identification	Ø	Item no.
	5 mm	2 x 0,5 mm ²	Loudspeaker	4-6 mm	20272
	5,4 mm	–	Phone	4-6 mm	20365
				4-6 mm	30039
	7 mm	–	CAT5/6/7	6-9 mm	20273
	7 mm	1 x 6 mm ²	NYM-J	6-9 mm	20366
	8 mm	–	Coaxial	6-9 mm	30040
	9 mm	3 x 1,5 mm ²	NYM-O		
	10 mm	3 x 2,5 mm ²	NYM	9-13 mm	20367
	10 mm	1 x 10 mm ²	NYO-O	9-13 mm	30041
	10 mm	1 x 16 mm ²	NYM-O	9-15 mm	20274
	11 mm	7 x 1,5 mm ²	NYM-O	9-15 mm	20266
	11 mm	5 x 2,5 mm ²	NYM	10 - 15 mm	20661
	11 mm	5 x 1,5 mm ²	NYO		
	13 mm	3 x 2,5 mm ²	NYO		
	14 mm	1 x 35 mm ²	NYO-O		
	15 mm	12 x 1,5 mm ²	NYM-JZ		
	15 mm	7 x 2,5 mm ²	NYM		
	15 mm	3 x 6 mm ²	NYM-J		
	15 mm	–	CAT6 duplex		
	17 mm	16 x 1,5 mm ²	NYM-J	15-19 mm	20267
	17 mm	5 x 6 mm ²	NYM-J	15 - 20 mm	20662
	18 mm	4 x 10 mm ²	NYM-J		
	18 mm	1 x 95 mm ²	NYO		
	20 mm	10 x 2,5 mm ²	NYCY	19-25 mm	20268
	21 mm	5 x 10 mm ²	NYO-J	20 - 25 mm	20663
	22 mm	12 x 2,5 mm ²	NYCY		
	22 mm	4 x 16 mm ²	NYM-J		
	24 mm	7 x 6 mm ²	NYCY		
	25 mm	1 x 185 mm ²	NYO		
	28 mm	3 x 35 mm ²	NYCWY	25-31 mm	20269
	29 mm	24 x 2,5 mm ²	NYCY	25 - 30 mm	20664
	32 mm	1 x 300 mm ²	NYO	30-40 mm	20436
	33 mm	40 x 2,5 mm ²	NYO-JZ		20665
	34 mm	5 x 35 mm ²	NYM-J		
	40 mm	3 x 95 mm ²	NYCWY		
	45 mm	3 x 120 mm ²	NYCWY	40-50 mm	20437
	47 mm	3 x 150 mm ²	NYCWY		20666
	52 mm	5 x 95 mm ²	NYO-J	50-60 mm	20438
	54 mm	3 x 185 mm ²	NYCWY		20667
	60 mm	3 x 240 mm ²	NYCWY		
	63 mm	4 x 240 mm ²	NYO-J	60-70 mm	20439
					20668

GF4.5 Fiberglass rod Ø 4.5 mm – Cable pulling system



VIDEO

GF4.5

KG 220

PATENTED

RC2 / RC3 – Inspection camera COMPATIBLE



Profi-Set

Ergonomic holding and carrying handle

Lateral parking brake


RG7 - Guiding head with front thread and eyelet

Double run-out system, quick outlet and automatic run-out brake

Extendable standing feet and storage compartment incl. accessories




Beginning: RG7 - Guiding head with swivel Ø 7 mm, RTG Ø 6 mm thread, screwed to strand



Ending: Ending joint, stainless steel, RTG Ø 6 mm thread





Attention! electric conductive

Included in the Profi-Set:
Extendable standing feet a. storage compartment incl. accessories



Included in the Profi-Set and Standard-Set:
Lateral parking brake and double run-out system (quick outlet and automatic run-out brake)



Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
4,5 mm	30 – 80 mm	120 mm	55 mm	1300 kg	220 kg

Item		Length	Item no.	Rec. trade price
	GF4.5 Fiberglass rod Ø 4.5 mm – Profi-Set	30 m	10052	260,00 €
	• Extendable feet with storage compartment incl. extensive accessories*	40 m	10055	287,00 €
	• Double run-out system and lateral parking brake	50 m	10057	315,00 €
	• RG7 - Guiding head with front thread and eyelet incl. swivel	60 m	10047	341,00 €
	• Robust CDP / powder-coated steel reel	80 m	10050	396,00 €
	Dimensions: L 360 mm W 250 mm H 460 mm			
	GF4.5 Fiberglass rod Ø 4.5 mm – Standard-Set	30 m	10054	192,00 €
	• Double run-out system and lateral parking brake	40 m	10056	218,00 €
	• RG7 - Guiding head with front thread and eyelet incl. swivel	50 m	10058	244,00 €
	• Robust CDP / powder-coated steel reel	60 m	10048	269,00 €
		80 m	10051	325,00 €
	Dimensions: L 360 mm W 250 mm H 440 mm			

GF4.5 - Cable pulling system - special offers - accessories - spare parts

30m + 60m

Accessories included in the storage compartment

SPECIAL OFFER

1 x RP5 without meter counter - 30 m, description page 26

1 x GF4.5 Fiberglass rod Ø 4,5 mm - 60 m incl. steel cage

INSTEAD OF € 503,00

€ 411,-
plus VAT.

RP5 - 30 m - GF4.5 - 60 m - offer
RUNPOTEC item no. 11120

50m + 50m

SPECIAL OFFER

1 x GF4.5 Fiberglass rod Ø 4,5 mm - 50 m,

1 x RC2 Inspection camera - 50 m, in the system case, description page 22

INSTEAD OF € 923,00


€ 789,-
plus VAT.

RC2 - 50 m - GF4.5 - 50 m - offer
RUNPOTEC item no. 11140


Item		Ø mm	Length	Item no.	Rec. trade price
	GF4.5 Replacement fiberglass rod Ø 4,5 mm with ending joints on both sides RTG Ø 6 mm thread		30 m	20311	82,00 €
			40 m	20312	97,00 €
			50 m	20313	113,00 €
			60 m	20314	131,00 €
			80 m	20315	162,00 €
 Video RG - RUNPOGLIDER guiding head	RG7 - Guiding head with front thread and eyelet Ø 7 mm incl. swivel stainless steel, RTG Ø 6 mm thread			20460	29,00 €
 Symbol picture	Flexible starting head stainless steel RTG Ø 6 mm thread	7 10 13		20116 20303 20119	8,00 € 8,20 € 8,20 €
 Information: Cable pulling grip range see page 38	Cable pulling grip with swivel stainless steel RTG Ø 6 mm thread	9 – 15 15 – 19 19 – 25 25 – 31		20266 20267 20268 20269	41,20 € 43,30 € 44,30 € 46,40 €
 NON-FLAMMABLE Tip: Ask for the package price	Cable lubricant SPRAY Cable lubricant FOAM (with folding spray tube) Non flammable	400 ml 400 ml		20523 20522	8,20 € 7,10 €
	Cable lubricant GEL Cable lubricant GEL	1000 g 250 g		30064 30467	8,90 € 4,40 €

GF4.5 - Cable pulling system - accessories - spare parts

Item		Item no.	Rec. trade price
	Roller Ø 25 mm stainless steel / aluminium RTG Ø 6 mm thread	20279	18,50 €
	Shackle stainless steel / galvanised steel RTG Ø 6 mm thread	20280	15,50 €
  Repair manual www.runpotec.com	GF4.5 Repairing-kit for Ø 4,5 mm 1 x special glue 3 g, 1 x coupling joint, 2 x ending joint RTG Ø 6 mm	20250	22,70 €
 	GF4.5 Ending joint-set for Ø 4,5 mm stainless steel, RTG Ø 6 mm thread PU = 3 ending joint	20322	11,30 €
 	GF4.5 Coupling joint-set for Ø 4,5 mm stainless steel PU = 3 coupling joint	20323	14,40 €
 	Eyelet Ø 8 mm stainless steel, RTG Ø 6 mm thread	30208	4,90 €
 	Eyelet-set Ø 7 mm stainless steel, RTG Ø 6 mm thread	20487	9,40 €
 	Swivel joint Ø 11 mm stainless steel, RTG Ø 6 mm thread	20251	24,70 €
 	Pull loop , stainless steel rope RTG Ø 6 mm thread Ø 1,5 mm (loop length 75 mm) Ø 2 mm (loop length 35 mm)	20428 20427	7,10 € 7,10 €
	Special glue 3 g	30050	8,40 €
	2 components special glue 24 ml	30067	20,60 €
	Pulling grip for fiberglass rod Ø 3 – 6 mm	30070	6,40 €
	Extendable standing feet incl. storage compartment for reel Ø 330 mm and Ø 530 mm	20278	43,30 €
	GF4.5 Profi-set steel reel Ø 330 mm for Ø 4,5 mm incl. double run-out system with extendable standing feet and storage compartment for accessories CDP/powder coated	20402	183,00 €
	GF4.5 Standard-set steel reel Ø 330 mm for Ø 4,5 mm incl. double run-out system and parking brake CDP/powder coated	20002	133,00 €

GF6 Fiberglass rod Ø 6 mm – Cable pulling system

Included in the Profi-Set:
Extendable standing feet a. storage compartment incl. accessories



Included in the Profi-Set and Standard-Set:
Lateral parking brake and double run-out system (quick outlet and automatic run-out brake)



Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
6 mm	40 – 100 mm	168 mm	80 mm	2200 kg	320 kg

Item		Length	Item no.	Rec. trade price
	GF6 Fiberglass rod Ø 6 mm – Profi-Set	40 m	10059	321,00 €
	• Extendable feet with storage compartment incl. extensive accessories*	50 m	10061	349,00 €
	• Double run-out system and lateral parking brake	60 m	10063	381,00 €
	• RG7 - Guiding head with front thread and eyelet incl. swivel	80 m	10065	448,00 €
	• Robust CDP / powder-coated steel reel Dimensions: L 550 mm W 220 mm H 655 mm			
	GF6 Fiberglass rod Ø 6 mm – Standard-Set	40 m	10060	265,00 €
	• Double run-out system and lateral parking brake	50 m	10062	293,00 €
	• RG7 - Guiding head with front thread and eyelet incl. swivel	60 m	10064	325,00 €
	• Robust CDP / powder-coated steel reel Dimensions: L 550 mm W 220 mm H 630 mm	80 m	10066	390,00 €

GF6 - Cable pulling system - accessories - spare parts

Item		Item no.	Rec. trade price
	GF6 Replacement fiberglass rod Ø 6 mm with ending joints on both sides RTG Ø 6 mm thread 40 m 50 m 60 m 80 m	20317	106,00 €
		20318	129,00 €
		20319	148,00 €
		20320	188,00 €
 Video RG - RUNPOGLIDER guiding head 	RG7 - Guiding head with front thread and eyelet Ø 7 mm incl. swivel stainless steel, RTG Ø 6 mm thread	20460	29,00 €
 	Flexible starting head Ø 7 mm stainless steel, RTG Ø 6 mm thread	20116	8,00 €
 	Flexible starting head Ø 10 mm stainless steel, RTG Ø 6 mm thread	20303	8,20 €
 	Flexible starting head Ø 13 mm stainless steel, RTG Ø 6 mm thread	20119	8,20 €
 Information: Cable pulling grip range see page 38	Cable pulling grip with swivel stainless steel, RTG Ø 6 mm thread Ø 9 – 15 mm Ø 15 – 19 mm Ø 19 – 25 mm Ø 25 – 31 mm	20266 20267 20268 20269	41,20 € 43,30 € 44,30 € 46,40 €
	Roller Ø 25 mm stainless steel / aluminium RTG Ø 6 mm thread	20279	18,50 €
	Shackle stainless steel / galvanised steel RTG Ø 6 mm thread	20280	15,50 €
 Repair manual, www.runpotec.com	GF6 Repairing-kit for Ø 6 mm 1 x 2K-special glue 24 ml 2 x Ending joints, RTG Ø 6 mm thread 1 x Coupling joint	20252	40,20 €
 	GF6 Ending joint-set for Ø 6 mm stainless steel, RTG Ø 6 mm thread PU = 2 ending joint	20316	12,40 €
 	GF6 Coupling joint-set for Ø 6 mm stainless steel PU = 2 coupling joint	20321	14,40 €
 	Pulling eyelet Ø 8 mm stainless steel, RTG Ø 6 mm thread	30208	4,90 €
 	Pulling eyelet-set Ø 7 mm stainless steel, RTG Ø 6 mm thread	20487	9,40 €
 	Swivel joint Ø 11 mm stainless steel, RTG Ø 6 mm thread	20251	24,70 €

GF6 - Cable pulling system - accessories - spare parts

Item		Item no.	Rec. trade price
		Pull loop , stainless steel rope Ø 1,5 mm (loop length 75 mm) RTG Ø 6 mm thread	20428 7,10 €
		Pull loop 2 mm , stainless steel rope Ø 2 mm (loop length 35 mm) RTG Ø 6 mm thread	20427 7,10 €
		Special glue 3 g	30050 8,40 €
		2 components special glue 24 ml	30067 20,60 €
		Pulling grip for fiberglass rod Ø 3 – 6 mm	30070 6,40 €
		Extendable standing feet incl. storage compartment for reel Ø 330 mm and Ø 530 mm PU = 1 piece	20278 43,30 €
		GF6 Profi-set steel reel Ø 530 mm for Ø 6 mm incl. double run-out system with extendable standing feet and storage compartment for accessories CDP/powder coated	20403 231,00 €
		GF6 Standard-set steel reel Ø 530 mm for Ø 6 mm incl. double run-out system and parking brake CDP/powder coated	20300 171,00 €
 NON-FLAMMABLE Tip: Ask for the package price		Cable lubricant SPRAY 400 ml	20523 8,20 €
		Cable lubricant FOAM 400 ml (with folding spray tube) Non flammable	20522 7,10 €
		Cable lubricant GEL 1000 g	30064 8,90 €
		Cable lubricant GEL 250 g	30467 4,40 €

Information


GF4.5 and GF6 Fiberglass rods Ø 4,5 mm, Ø 6 mm, the RUNPOSTICKS and the entire accessories are compatible! s.p.28

FLEXIBLE LEADING HEAD-SET for GF7,5 / GF9 / GF11 / GF15

Flexible leading head-set: can be adapted on roller, shackle and starting head Ø 20 mm and Ø 30 mm.

**Connectivity options:**

The sticks can each be extended by 1 m and adapted as flexible leading head-set on fiberglass rods Ø 7,5 mm, Ø 9 mm, Ø 11 mm and Ø 15 mm to get around narrow bends. It is additionally possible to screw on accessories such as the roller or guiding head with swivel at the tip.

**Application example: flexible leading head-set****The problem situation:**




Fiberglass rod Ø 7,5 mm, Ø 9 mm, Ø 11 mm or Ø 15 mm stops at to narrow radii from of the tube.

Solution:

With leading head-set, taper off through the flexible sticks Ø 4,5 mm (yellow), Ø 5,5 mm (black) oder Ø 7,5 mm (red). Thereby it makes it possible to get over the last bend or radii.

Tooltip:

Additional manual haul support possible.



Item		Item. no.	Rec. trade price
	Flexible leading head-set – 13 parts Included accessories of flexible leading head-set with RTG Ø 6 mm thread: 2 x Sticks Ø 4,5 mm, 2 x Sticks Ø 5,5 mm, 2 x Sticks Ø 7,5 mm, 1 x RG7 - Guiding head with front thread, Roller Ø 24 mm, 3 x Coupling thread, 1 x Blindcap, 1 x Starting head Ø 20 mm	20442	102,00 €

GF7.5 / GF9 Fiberglass rod Ø 7,5 / 9 mm – Cable pulling system

Ergonomic holding and carrying handle

Autom. run-out brake

Lateral parking brake

Meter counter with hardened thumb wheel

Quick run with mounted rollers

Mobile reel
CDP / powder-coated

2 x threaded bolts
(for roller or starting head)




Rod tip: Shackle, stainless steel,
RTG Ø 12 mm thread,
screwed to strang



Rod end: Ending joint, stainless steel,
RTG Ø 12 mm thread

Double run-out-system (Quick run and automatic run-out brake)

Quick run with mounted rollers



Automatic run-out brake




Meter counter with hardened thumb wheel

6-digit roller counter with meter
and 10 cm steps



Additional option: Adaptable leading heads



13-parts flexible leading head-set
see page 46



Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
7,5 mm	50 – 120 mm	500 mm	115 mm	3400 kg	400 kg
9 mm	60 – 200 mm	620 mm	140 mm	4500 kg	460 kg

Item		Length	Item. no.	Rec. trade price
	GF7.5 Fiberglass rod Ø 7,5 mm, mobile, Ø 730 mm	40 m	10076	455,00 €
	• Meter counter with hardened thumb wheel	50 m	10077	477,00 €
	• Double run-out-system with parking brake	60 m	10078	497,00 €
	• Rod tip with shackle	80 m	10079	539,00 €
	• Robust CDP / powder-coated steel reel	100 m	10080	576,00 €
	Dimensions: L 820 mm W 400 mm H 900 mm	120 m	10091	610,00 €
	GF9 Fiberglass rod Ø 9 mm, mobile, Ø 730 mm	40 m	10081	458,00 €
	• Meter counter with hardened thumb wheel	50 m	10082	489,00 €
	• Double run-out-system with parking brake	60 m	10083	519,00 €
	• Rod tip with shackle	80 m	10084	576,00 €
	• Robust CDP / powder-coated steel reel	100 m	10085	624,00 €
	Dimensions: L 820 mm W 400 mm H 730 mm	120 m	10086	656,00 €
		150 m	10110	747,00 €

GF7.5 / GF9 - Cable pulling system - accessories - spare parts

Item		Item no.	Rec. trade price
	GF7.5 Replacement fiberglass rod Ø 7.5 mm , ending joints on both sides RTG Ø 12 mm thread		
	40 m	20368	130,00 €
	50 m	20369	146,00 €
	60 m	20370	166,00 €
	80 m	20371	207,00 €
	100 m	20372	244,00 €
	120 m	20414	281,00 €
	GF9 Replacement fiberglass rod Ø 9 mm , ending joints on both sides RTG Ø 12 mm thread		
	40 m	20373	144,00 €
	50 m	20374	171,00 €
	60 m	20375	199,00 €
	80 m	20376	247,00 €
	100 m	20377	309,00 €
	120 m	20378	350,00 €
	Roller Ø 50 mm stainless steel / aluminium RTG Ø 12 mm thread incl. connection thread and blind cap		
		20382	40,20 €
	 Cross section RTG Ø 12 mm RTG Ø 6 mm incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection)		
			
	Shackle stainless steel, galvanised steel RTG Ø 12 mm thread incl. connection thread and blind cap		
		20383	27,80 €
	 Cross section RTG Ø 12 mm RTG Ø 6 mm incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection)		
	Starting head Ø 30 mm stainless steel, RTG Ø 12 mm thread incl. connection thread and blind cap		
		20404	25,80 €
	 Cross section RTG Ø 12 mm RTG Ø 6 mm incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection)		
			
	Starting head Ø 20 mm stainless steel, RTG Ø 12 mm thread incl. connection thread and blind cap		
		20409	23,70 €
	 Cross section RTG Ø 12 mm RTG Ø 6 mm incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection)		
	Swivel joint Ø 25 mm stainless steel, RTG Ø 12 mm thread		
		20387	36,10 €
			
	Meter counter for steel reel Ø 730 mm incl. mounting-set		
		20461	109,00 €
			
	Run-out rollers-set (set of 4) for reel Ø 730 mm and Ø 1000 mm incl. fixing-set		
		20646	31,90 €
	GF7.5 / GF9 Repairing-kit 1 x 2K-special glue 24 ml 2 x Ending joints, RTG Ø 12 mm thread 1 x Coupling joint for Ø 7,5 mm		
		20384	47,40 €
	for Ø 9 mm	20385	53,00 €

Repair manual, www.runpotec.com

GF7.5 / GF9 - Cable pulling system - accessories - spare parts

Item		Item no.	Rec. trade price
 	GF7.5 / GF9 Ending joint stainless steel, RTG Ø 12 mm thread for Ø 7,5 mm for Ø 9 mm	20381	10,30 €
		20379	10,30 €
 	GF7.5 / GF9 Coupling joint stainless steel for Ø 7,5 mm for Ø 9 mm	20380	14,40 €
		20412	14,40 €
 	Blind cap-set stainless steel, RTG Ø 6 mm thread PU = 3 blind cap-set	20443	6,00 €
	2 components special glue 24 ml	30067	20,60 €
	GF7.5 / GF9 Steel reel Ø 730 mm , mobile for Ø 7,5 mm and 9 mm incl. double run-out system and meter counter CDP/powder coated	20405	330,00 €
  Information: Cable pulling grip range see page 38	Cable pulling grip with swivel stainless steel, RTG Ø 12 mm thread Ø 9 – 15 mm Ø 15 – 19 mm Ø 19 – 25 mm Ø 25 – 31 mm	20266	41,20 €
		20267	43,30 €
		20268	44,30 €
		20269	46,40 €
 Information: Flexible leading head-set see page 46	Flexible leading head-set - 13 parts, RUNPOSTICKS including accessories stowed in storage bag	20442	102,00 €
 NON-FLAMMABLE Tip: Ask for the package price	Cable lubricant SPRAY 400 ml Cable lubricant FOAM 400 ml (with folding spray tube) Non flammable	20523	8,20 €
		20522	7,10 €
	Cable lubricant GEL 1000 g Cable lubricant GEL 250 g	30064	8,90 €
		30467	4,40 €
	Cable lubricant LIQUID 1000 ml	30063	7,40 €

RC2 / RC3 Inspection camera compatible

The RC2/RC3 Inspection camera – is also compatible with GF7.5, GF9, GF11 and GF15 Fiberglass rod Ø 7,5 mm, Ø 9 mm, Ø 11 mm and Ø 15 mm. This allows the coupling thread RTG Ø 12 mm to RTG Ø 6 mm thread. See page 22

GF11 Fiberglass rod Ø 11 mm – Cable pulling system

Ergonomic holding and carrying handel

Autom. Run-out brake

Lateral parking brake

Meter counter with hardened thumb wheel

Quick run with mounted rollers

Mobile reel
CDP/ powder-coated

2 x threaded bolts
(for roller or starting head)




Rod tip: Shaket, stainless steel,
RTG Ø 12 mm thread,
screwed to strang



Rod end: Ending joint, stainless steel,
RTG Ø 12 mm thread

Double run-out-system (Quick run and automatic run-out brake)

Quick run with mounted rollers




Automatic run-out brake




Meter counter with hardened thumb wheel

6-digit roller counter with meter
and 10 cm steps



Additional option: Adaptable leading heads




13-parts flexible leading head-set
see page 46



Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
11 mm	80 – 250 mm	770 mm	210 mm	6200 kg	580 kg

Item		Length	Item no.	Rec. trade price
	GF11 Fiberglass rod Ø 11 mm , mobile, Ø 1000 mm • Meter counter with hardened thumb wheel • Double run-out-system with parking brake • Rod tip with shackle • Robust CDP / powder-coated steel reel Dimensions: L 1140 mm W 550 mm H 1200 mm	100 m	10092	758,00 €
		120 m	10093	831,00 €
		150 m	10094	936,00 €
		200 m	10095	1118,00 €
		250 m	10096	1306,00 €
		300 m	10097	1410,00 €
	GF11 Replacement fiberglass rod Ø 11 mm with ending joints on both sides RTG Ø 12 mm thread Dimensions: Ø 1060 mm H 245 mm	100 m	20386	523,00 €
		120 m	20417	535,00 €
		150 m	20418	665,00 €
		200 m	20419	832,00 €
		250 m	20420	983,00 €
		300 m	20421	1144,00 €

GF11 - Cable pulling system - accessories - spare parts

Item	Item no.	Rec. trade price
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Roller Ø 50 mm stainless steel / aluminium RTG Ø 12 mm thread incl. connection thread and blind cap	20382 40,20 €
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Shackle stainless steel, galvanised steel RTG Ø 12 mm thread incl. connection thread and blind cap	20383 27,80 €
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Starting head Ø 30 mm stainless steel, RTG Ø 12 mm thread incl. connection thread and blind cap	20404 25,80 €
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Starting head Ø 20 mm stainless steel, RTG Ø 12 mm thread incl. connection thread and blind cap	20409 23,70 €
 	Swivel joint Ø 25 mm stainless steel, RTG Ø 12 mm thread	20387 36,10 €
	Meter counter for steel reel Ø 1000 mm incl. mounting-set	20462 115,00 €
	Run-out rollers-set (set of 4) for reel Ø 730 mm and Ø 1000 mm incl. fixing screws	20646 31,90 €
   Repair manual, www.runpotec.com	GF11 Repairing-kit for Ø 11 mm 1 x 2K-special glue 24 ml 2 x Ending joints, RTG Ø 12 mm thread 1 x Coupling joint	20424 61,00 €
 	GF11 Ending joint for Ø 11 mm stainless steel, RTG Ø 12 mm thread	20422 12,40 €
 	GF11 Coupling joint for Ø 11 mm stainless steel	20423 17,50 €
 	Blind cap-set stainless steel, RTG Ø 12 mm thread 3 pieces	20443 6,00 €
	2 components special glue 24 ml	30067 20,60 €
	GF11 Steel reel for Ø 11 mm incl. double run-out system and meter counter CDP / powder coated mobile, Ø 1000 mm	20416 411,00 €

Information



Compatible cable pulling grip range see page 37.

GF15 Fiberglass rod Ø 15 mm – Cable pulling system





Robust steel reel galvanized
Basket CDP/ powder-coated

Lateral parking brake

Meter counter with
hardened thumb wheel


Run-out with mounted
rollers

Mobile reel

2 x threaded bolts
(for roller or starting head)



Rod tip: Shackle, stainless steel, RTG Ø 12 mm thread, screwed to strang




Rod end: Ending joint, stainless steel, RTG Ø 12 mm thread

Meter counter with hardened thumb wheel
6-digit roller counter with meter and 10 cm steps




Run-out-system with rollers and Lateral parking brake


Run-out with mounted rollers








Lateral parking brake







Additional option:
Adaptable leading heads
13-parts flexible leading head-set see page 46



Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
15 mm	180 – 450 mm	1200 mm	800 mm	14500 kg	690 kg

Item		Length	Item no.	Rec. trade price
	GF15 Fiberglass rod Ø 15 mm, mobile, Ø 1400 mm	150 m	10099	2547,00 €
	• Meter counter with hardened thumb wheel	200 m	10100	2808,00 €
	• Run-out-system with rollers and lateral parking brake	250 m	10101	3093,00 €
	• Rod tip with shackle	300 m	10102	3354,00 €
	• Robust steel reel - galvanized	350 m	10103	3639,00 €
	• Reel basket - CDP / powder-coated	400 m	10104	3933,00 €
	Dimensions: L 1558 mm W 628 mm H 1593 mm			
	GF15 Replacement fiberglass rod Ø 15 mm	150 m	20491	1029,00 €
	with ending joints on both sides	200 m	20492	1272,00 €
	RTG Ø 12 mm thread	250 m	20493	1545,00 €
	Dimensions: Ø 1470 mm H 334 mm	300 m	20494	1815,00 €
		350 m	20495	2081,00 €
		400 m	20496	2394,00 €

GF15 - Cable pulling system - accessories - spare parts

Item	Item no.	Rec. trade price
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Roller Ø 50 mm stainless steel / aluminium RTG Ø 12 mm thread incl. connection thread and blind cap	20382 40,20 €
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Shackle stainless steel, galvanised steel RTG Ø 12 mm thread incl. connection thread and blind cap	20383 27,80 €
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Starting head Ø 30 mm stainless steel, RTG Ø 12 mm thread incl. connection thread and blind cap	20404 25,80 €
 Cross section  incl. connection thread (for flexible leading head or small-sized cable pulling grip) including blind cap (for thread protection) RTG Ø 12 mm RTG Ø 6 mm	Starting head Ø 20 mm stainless steel, RTG Ø 12 mm thread incl. connection thread and blind cap	20409 23,70 €
 	Swivel joint Ø 25 mm stainless steel, RTG Ø 12 mm thread	20387 36,10 €
   Repair manual, www.runpotec.com	GF15 Repairing-kit for Ø 15 mm 1 x 2K-special glue 24 ml 2 x Ending joints, RTG Ø 12 mm thread 1 x Coupling joint	20489 177,00 €
 	GF15 Ending joint for Ø 15 mm stainless steel, RTG Ø 12 mm thread	20490 57,00 €
 	GF15 Coupling joint for Ø 15 mm stainless steel	20498 58,00 €
	2 components special glue 24 ml	30067 20,60 €
	GF15 Steel reel for Ø 15 mm incl. meter counter Steel reel - galvanized Reel basket - CDP / powder-coated mobile, Ø 1400 mm	20497 1639,00 €
 Information: Flexible leading head-set see page 46	Flexible leading head-set - 13 parts, RUNPOSTICKS including accessories stowed in storage bag	20442 102,00 €

Information



Compatible cable pulling grip range see page 37.

CW 800 E Capstan winch for horizontal cable pulling

CW 800 E



EXTRA STRONG, provides the pulling power of 8 – 10 people

Rope pulley (capstan) small
Ø 55 mm, 4 m/min., max. 800 kg

Rope pulley (capstan) large
Ø 110 mm, 8 m/min., max. 400 kg

Trolley mounting rail with
2 wheels and many mounting
options

Belt (3 m) with loops including
2 fastening shackles

SPECIAL OFFER

CW 800 E + 1x cable pulling
grip + 1x cable guide roller –
shaft for free! See page 68

The CW 800 E Capstan winch is ideal for pulling one or more cables horizontally. One person is enough to move at either 4 m/min | max. 800 kg or 8 m/min | max. 400 kg to pull the cables. The CW 800 E can be attached to objects using the mounting holes, with the strap, or on the trolley mounting rail using the two fixing bolts. The trolley mounting rail itself can be attached to the trailer hitch of cars through the special coupling opening, and mounted horizontally or vertically.



Safety notice: Not suitable for vertical cable pulling, must not be used to carry or lift loads or persons.

Item		Item no.	Rec. trade price
	CW 800 E Capstan winch for horizontal cable pulling incl. steel trolley mounting rail and 3 m strap Total weight: 41,5 kg Motor connection: 230 V 50 Hz Motor power: 0,75 KWh 5,1 A Dimensions: L 990 mm W 370 mm H 360 mm	10138	2368,00 €
	CW 800 E Capstan winch for horizontal cable pulling Total weight: 32 kg Motor connection: 230 V 50 Hz Motor power: 0,75 KWh 5,1 A Dimensions: L 510 mm W 370 mm H 350 mm	10148	2270,00 €
	Trolley mounting rail for capstan winch CW 800 E - easy to transport due to wheels and ergonomic handle, versatile mounting options - steel galvanised	20622	143,00 €
	Capstan head Spare part for CW 800 E capstan winch Diameter Ø 55 mm – Tension load 800 kg Diameter Ø 110 mm – Tension load 400 kg	20658 20657	162,00 € 196,00 €
	Rope guide jaw-set Spare part for CW 800 E capstan winch Ø 55 mm / Ø 110 mm	20683	114,00 €

CW 800 E Capstan winch - mounting and application examples


The portable CW 800 E Capstan winch can be fastened in various ways:

The housing can be screwed to the floor **1**, or with a strap and suitable accessories through the attachment eye **2** fixed to a solid object (e.g., tree). You can also fix the housing on the trolley **3** by means of locking bolts **4** on the rail. The trolley itself can be screwed down, hung directly on a trailer hitch **5** or fixed with a strap through the attachment eye to a fixed object.




Application of the CW 800 E Capstan winch:


The cable to be pulled is connected, preferably with a connection swirl with swivel, with the pull rope.



The towing rope is guided past inside the rope guide pin **6**. Wrap the towing rope at least 3 times around the capstan winch (**7** or **8**) and then lead out through the rope guide **9**. Keep the towing rope tight, so that it does not get tangled up.



The operator stands next to the capstan winch with a sufficient safety distance and pulls with little effort at a 90° angle to the pulling direction on the pull rope. The effort should only be so strong until the feed rate is reached. Very strong pulling does not increase the pulling power of the capstan winch!



POLYESTER CABLE PULLING ROPE incl. steel reel

KG
1100

Steel reel 514/70



KG
1640

Steel reel 770/98



KG
2180

Steel reel 770/192

The **polyester pulling rope** Ø 10 mm and Ø 12 mm is suitable for horizontal cable pull with the CW 800 E Capstan winch. For the horizontal cable pull, the use of the connection swivel with twist compensation is recommended, it reduces the frictional resistance and thus protects the cable and pull-in system. The steel reel enables controlled winding and unwinding of the rope.

Safety notice: Not suitable for the vertical cable pull, must not be used to bear/lift loads or people.

*Pulling rope Ø 8 mm is not suitable for pulling the cable with the CW 800 E Capstan winch.

Item		Rope Ø	Total breaking load	Length	Reel basket Ø	Internal reel basket	Item no.	Rec. trade price
	Pulling rope incl. steel reel and parking brake CDP / powder coated Spliced loops at the start and end of the rope	* 8 mm	1100 kg	120 m	514 mm	70 mm	10169	380,00 €
		10 mm	1640 kg	120 m	514 mm	70 mm	10167	428,00 €
				200 m	770 mm	98 mm	10168	582,00 €
		12 mm	2180 kg	150 m	770 mm	98 mm	10120	606,00 €
				200 m	770 mm	98 mm	10121	677,00 €
				300 m	770 mm	192 mm	10122	821,00 €
				350 m	770 mm	192 mm	10123	916,00 €

Item		Rope Ø	Total breaking load	Length	Reel basket Ø	Drum height	Item no.	Rec. trade price
	Pulling rope on drum Spliced loops at the start and end of the rope	* 8 mm	1100 kg	120 m	230 mm	217 mm	20621	131,00 €
		10 mm	1640 kg	120 m	250 mm	212 mm	20619	178,00 €
				200 m	300 mm	340 mm	20620	262,00 €
		12 mm	2180 kg	150 m	300 mm	340 mm	20615	272,00 €
				200 m	350 mm	342 mm	20616	356,00 €
				300 m	400 mm	370 mm	20617	510,00 €
				350 m	400 mm	425 mm	20618	595,00 €

Item		Reel basket Ø	Internal reel basket	Item no.	Rec. trade price
	Rope reel 514	514 mm	70 mm	20527	259,00 €
	Rope reel 770 small	770 mm	98 mm	20526	335,00 €
	Rope reel 770 wide	770 mm	192 mm	20525	340,00 €

Item		Weave length	Total breaking load	Ø	Item no.	Rec. trade price
 Weave length Application example 	Cable pulling grip with loop	600 mm	1019 kg	Ø 10 – 15 mm	20661	41,20 €
		600 mm	2080 kg	Ø 15 – 20 mm	20662	43,30 €
		600 mm	2080 kg	Ø 20 – 25 mm	20663	44,30 €
		1000 mm	2080 kg	Ø 25 – 30 mm	20664	48,40 €
		1250 mm	3059 kg	Ø 30 – 40 mm	20665	55,00 €
		1250 mm	4078 kg	Ø 40 – 50 mm	20666	60,00 €
		1500 mm	4996 kg	Ø 50 – 60 mm	20667	70,00 €
		1500 mm	4996 kg	Ø 60 – 70 mm	20668	82,00 €
		1500 mm	4996 kg	Ø 70 – 85 mm	20669	96,00 €
		1500 mm	5812 kg	Ø 85 – 100 mm	20670	109,00 €
		Optimal combination: Pulling rope – connection swirl with swivel – cable pulling grip				

ACCESSORIES – Optimal in combination with pulling rope, cable pulling grip and CW 800 E Capstan winch





Item		Item no.	Rec. trade price
	Connection swirl with swivel Ø 30 mm L 132 mm, stainless steel	10176	196,00 €

CABLE GUIDE ROLLER



Cable guide roller can be used for shafts, cable trays, pillars, etc. to gently pull cables around corners with the least possible resistance. The high-quality aluminum heavy-duty rollers with integrated ball bearings and the stable powder-coated steel frame guarantee a long service life.



Item		Item no.	Rec. trade price
	Cable guide roller – chain – 3 roll links Universally applicable for shafts, cable routes, pillars etc., load capacity 4.500 kg Roller-Ø 130 mm, max. cable diameter: Ø 100 mm Aluminium heavy-duty rollers, frame: CDP and powder coated	10166	241,00 €
	Cable guide roller – chain – 4 roll links Description see 3 roll links	10199	321,00 €
	Cable guide roller – chain – 5 roll links Description see 3 roll links	10200	402,00 €
	Cable guide roller – chain – 6 roll links Description see 3 roll links	10201	481,00 €
 	Cable guide roller – shaft for shaft inlets or outlets , load capacity 4.500 kg Roller-Ø 130 mm, max. cable diameter: Ø 100 mm Aluminium heavy-duty rollers, frame: CDP and powder coated	10157	82,00 €
 	Cable guide roller – shaft inside edge for shafts, shoulders or steps, load capacity 4.500 kg Roller-Ø 130 mm, max. cable diameter: Ø 100 mm Aluminium heavy-duty rollers, frame: CDP and powder coated	10156	82,00 €
 	Cable guide roller – 90 degrees for corners and edges, load capacity 4.500 kg Roller-Ø 130 mm, max. cable diameter: Ø 100 mm Aluminium heavy-duty rollers, frame: CDP and powder coated, ergonomic aluminium carrying handle	10153	157,00 €
 	Cable guide roller – 90 degrees 3 R for corners and edges, load capacity 2.500 kg Roller-Ø 130 mm, max. cable diameter: Ø 100 mm Aluminium heavy-duty rollers, frame: CDP and powder coated, ergonomic aluminium carrying handle	10189	247,00 €

RUNPOTEC SYSTEM CASE

W-BOXX® | Sortimo® COMPATIBLE

Stackable with fast click system



RUNPOTEC system case with UNIVERSAL, RC2 Inspections camera, RT 2008 and RM35 case insert is perfect for storing and transporting of the previously mentioned RUNPOTEC products. One advantage is the fast click system, which allows the boxes to be connected to each other without effort and disconnected again at the push of a button. The boxes are easily stackable thanks to the quick click system. The W-BOXX can be seamlessly integrated into the Sortimo Globelyst system. The high-quality and lightweight W-BOXX made of PP plastic is impact and shock resistant and splash-proof.

UNIVERSAL
case insert

symbol photo without content

RC2 Inspection camera
case insert

symbol photo without content

RT 2008
case insert

symbol photo without content

RM35
case insert

symbol photo without content

Item	Item no.	Rec. trade price
	20611	56,00 €
	20612	56,00 €
	20613	56,00 €
	20708	56,00 €

RUNPOTEC system case
with case insert for **RT 2008**

RUNPOTEC system case
with case insert for **RC2 Inspection camera**


RUNPOTEC system case
with **UNIVERSAL** case insert
For XB 300 + multifunction mandrel +
RP5 + small parts

RUNPOTEC system case
with case insert for **RM35**
For RM35 including accessories

RM80 Laser distance meter



POWERFUL LASER
up to 80 m



Front laser



Carrying loop



Protective case




Technical data

Measuring range	0,05 m – 80 m	IP rating	IP 54
Measuring tolerance	± 1,5 mm auf 80m	Laser type	620 – 690 nm, < 1mW
Laser class	II	Dimensions (mm)	121 x 45 x 25
Measure range of tilt sensor	360°	Battery	AAA 2 x 1,5 V
Accuracy of tilt sensor	± 0,3 ° *	Battery life	up to 5000 measurings

* This is the typical value. Depending on the enviroment the deviation can rise slightly.

Technical data



Item		Item no.	Rec. trade price
	RM80 Laser distance meter - Measures up to 80 m distance - Incl. angle- and inclination display - Extensive calculation functions - Storage of 99 measurings - Incl. protective case with belt loop	10108	118,00€

METAL SPIRAL with special eyelet







Beginning: Special eyelet Ø 6 mm, pressed onto strand

Ending: Special eyelet Ø 6 mm, pressed onto strand



3 times offset wound metal spiral

Rod	Rec. pipe ID*	Bending radius rod	Total breaking load - ending	Total breaking load - beginning
Ø				
4 mm	Ø 9 - 32 mm	25 mm	120 Kg	120 Kg

Item		Length	Item no.	Rec. trade price
	Metal spiral Ø 4 mm with special eyelet Total breaking load: 120 kg	10 m	30010	14,40 €
		15 m	30011	21,60 €
		20 m	30012	26,80 €
		25 m	30013	33,00 €
		30 m	30014	40,20 €

NYLON FISH TAPE





Beginning: starting spinner with eyelet Ø 6 mm, pressed onto strand

Ending: Special eyelet Ø 6 mm, pressed onto strand



Rod	Rec. pipe ID*	Bending radius rod	TBL - ending	Total breaking load - beginning
Ø				
4 mm	Ø 9 - 20 mm	25 mm	110 Kg	110 Kg

Item		Length	Item no.	Rec. trade price
	Nylon fish tape Ø 4 mm Total breaking load: 110 kg	5 m	20060	7,80 €
		10 m	20061	9,30 €
		15 m	20062	11,30 €
		20 m	20063	12,40 €
		25 m	20064	14,40 €
		30 m	20065	15,50 €

* ID = Inner diameter

Page	EAN-Code	Item no.	Rec. trade price
34	9120045476163	10000	308,00 €
26	9120045472806	10013	140,00 €
26	9120045472813	10014	162,00 €
28	9120045473094	10016	119,00 €
28	9120045473100	10020	139,00 €
29	9120045473186	10042	24,70 €
29	9120045473179	10043	19,00 €
29	9120045473162	10044	20,00 €
29	9120045473155	10045	20,00 €
40	9120045473520	10047	341,00 €
40	9120045473537	10048	269,00 €
40	9120045473544	10050	396,00 €
40	9120045473551	10051	325,00 €
40	9120045473568	10052	260,00 €
40	9120045473575	10054	192,00 €
40	9120045473582	10055	287,00 €
40	9120045473599	10056	218,00 €
40	9120045473605	10057	315,00 €
38	9120045473612	10058	244,00 €
43	9120045473629	10059	321,00 €
43	9120045473636	10060	265,00 €
43	9120045473643	10061	349,00 €
43	9120045473650	10062	293,00 €
43	9120045473667	10063	381,00 €
43	9120045473674	10064	325,00 €
43	9120045473681	10065	448,00 €
43	9120045473704	10066	390,00 €
47	9120045473858	10076	455,00 €
47	9120045473865	10077	477,00 €
47	9120045473872	10078	497,00 €
47	9120045473889	10079	539,00 €
47	9120045473896	10080	576,00 €
47	9120045473902	10081	458,00 €
47	9120045473919	10082	489,00 €
47	9120045473926	10083	519,00 €
47	9120045473933	10084	576,00 €
47	9120045473940	10085	624,00 €
47	9120045473957	10086	656,00 €
47	9120045474428	10091	610,00 €
50	9120045474480	10092	758,00 €
50	9120045474497	10093	831,00 €
50	9120045474503	10094	936,00 €
50	9120045474510	10095	1 118,00 €
50	9120045474527	10096	1 306,00 €
50	9120045474534	10097	1 410,00 €
52	9120045474749	10099	2 547,00 €

Page	EAN-Code	Item no.	Rec. trade price
52	9120045474756	10100	2 808,00 €
52	9120045474763	10101	3 093,00 €
52	9120045474770	10102	3 354,00 €
52	9120045474787	10103	3 639,00 €
52	9120045474794	10104	3 933,00 €
59	9120045474893	10108	118,00 €
47	9120045475210	10110	747,00 €
56	9120045475364	10120	606,00 €
56	9120045475371	10121	677,00 €
56	9120045475388	10122	821,00 €
56	9120045475395	10123	916,00 €
15	9120045475647	10134	199,00 €
15	9120045475654	10135	230,00 €
12	9120045475616	10136	234,00 €
10	9120045475623	10137	114,40 €
54	9120045475630	10138	2 368,00 €
22	9120045475555	10139	524,00 €
22	9120045475562	10140	566,00 €
22	9120045475579	10141	608,00 €
18	9120045475609	10142	864,00 €
16	9120045475708	10147	139,00 €
54	9120045475715	10148	2 270,00 €
57	9120045476361	10153	157,00 €
36	9120045475777	10154	42,20 €
57	9120045476378	10156	82,00 €
57	9120045476385	10157	82,00 €
36	9120045475821	10159	42,20 €
16	9120045476439	10161	2 153,00 €
16	9120045476446	10162	2 688,00 €
16	9120045476453	10163	2 730,00 €
16	9120045476460	10164	2 771,00 €
57	9120045476521	10166	241,00 €
56	9120045475906	10167	428,00 €
56	9120045475913	10168	582,00 €
56	9120045475920	10169	380,00 €
11	9120045476545	10170	195,00 €
11,27	9120045476552	10171	314,00 €
6	9120045476583	10172	349,00 €
11	9120045475685	10174	152,00 €
38,56	9120045475999	10176	196,00 €
7	9120045476910	10184	489,00 €
3,13	9120045477009	10187	310,00 €
57	9120045477047	10189	247,00 €
30	9120045476729	10192	184,00 €
4,30	9120045477122	10193	169,00 €
30	9120045477139	10195	219,00 €

Page	EAN-Code	Item no.	Rec. trade price
30	9120045477146	10196	117,50 €
30	9120045477153	10197	131,00 €
30	9120045477160	10198	156,50 €
57	9120045477214	10199	321,00 €
57	9120045477221	10200	402,00 €
57	9120045477238	10201	481,00 €
26	9120045477573	10202	170,00 €
3,26	9120045477580	10203	189,00 €
32	9120045477511	10207	182,00 €
4,32	9120045477528	10208	167,00 €
32	9120045477535	10209	217,00 €
32	9120045477542	10210	115,50 €
32	9120045477559	10211	129,00 €
32	9120045477566	10212	154,50 €
3,20	9120045477894	10214	299,00 €
9	9120045477924	10215	99,00 €
2,9	9120045477931	10216	369,00 €
2,9	9120045477993	10217	495,00 €
66	9120045476224	11117	186,00 €
27,41	9120045473353	11120	411,00 €
23,41	9120045476392	11140	789,00 €
66	9120045476651	11142	175,00 €
4	9120045476897	11143	390,00 €
67,23	9120045477177	11146	659,00 €
	9120045477443	11147	396,00 €
21	9120045477900	11149	429,00 €
21	9120045477917	11150	449,00 €
42	9120045473711	20002	133,00 €
34	9120045472585	20004	183,00 €
34	9120045470161	20010	8,20 €
34	9120045470253	20020	9,30 €
34	9120045470307	20025	9,30 €
34	9120045470376	20032	9,30 €
34	9120045470451	20040	9,30 €
28	9120045473049	20059	21,60 €
60	9120045472523	20060	7,80 €
60	9120045472530	20061	9,30 €
60	9120045472547	20062	11,30 €
60	9120045472554	20063	12,40 €
60	9120045472561	20064	14,40 €
60	9120045472578	20065	15,50 €
31,33	9120045474053	20108	7,20 €
41,44	9120045474077	20116	8,00 €
41,44	9120045474091	20119	8,20 €
29	9120045473209	20238	29,00 €
27	9120045472820	20240	110,00 €
27	9120045472837	20241	126,00 €


Page	EAN-Code	Item no.	Rec. trade price
27	9120045472844	20242	144,00 €
42	9120045473384	20250	22,70 €
42,44	9120045473391	20251	24,70 €
44	9120045473407	20252	40,20 €
34	9120045472868	20253	17,50 €
29	9120045473032	20260	9,30 €
24,29	9120045473018	20261	7,00 €
29	9120045473001	20262	10,30 €
41,44,49	9120045473728	20266	41,20 €
41,44,49	9120045473735	20267	43,30 €
41,44,49	9120045473742	20268	44,30 €
41,44,49	9120045473759	20269	46,40 €
25,27,37	9120045473292	20272	26,80 €
25,27,37	9120045473308	20273	29,90 €
25,27,37	9120045473315	20274	34,00 €
42,45	9120045474350	20278	43,30 €
42,44	9120045473230	20279	18,50 €
42,44	9120045474800	20280	15,50 €
45	9120045473766	20300	171,00 €
41,44	9120045474084	20303	8,20 €
41	9120045473438	20311	82,00 €
41	9120045473445	20312	97,00 €
41	9120045473452	20313	113,00 €
41	9120045473469	20314	131,00 €
41	9120045473476	20315	162,00 €
44	9120045473261	20316	12,40 €
44	9120045473483	20317	106,00 €
44	9120045473490	20318	129,00 €
44	9120045473506	20319	148,00 €
44	9120045473513	20320	188,00 €
44	9120045473414	20321	14,40 €
42	9120045473254	20322	11,30 €
42	9120045473421	20323	14,40 €
34	9120045473780	20333	8,20 €
31,37	9120045474114	20365	18,50 €
31,37	9120045474121	20366	19,60 €
31,37	9120045474138	20367	29,90 €
48	9120045474145	20368	130,00 €
48	9120045474152	20369	146,00 €
48	9120045474169	20370	166,00 €
48	9120045474176	20371	207,00 €
48	9120045474183	20372	244,00 €
48	9120045474190	20373	144,00 €
48	9120045474206	20374	171,00 €
48	9120045474213	20375	199,00 €
48	9120045474220	20376	247,00 €
48	9120045474237	20377	309,00 €

Page	EAN-Code	Item no.	Rec. trade price
48	9120045474244	20378	350,00 €
49	9120045474268	20379	10,30 €
49	9120045474275	20380	14,40 €
49	9120045474282	20381	10,30 €
48,51,53	9120045474299	20382	40,20 €
48,51,53	9120045474305	20383	27,80 €
48	9120045474312	20384	47,40 €
48	9120045474329	20385	53,00 €
50	9120045474541	20386	523,00 €
48,51,53	9120045474336	20387	36,10 €
38	9120045474343	20388	22,70 €
14	9120045477719	20401	148,00 €
42	9120045474374	20402	183,00 €
45	9120045474367	20403	231,00 €
48,51,53	9120045474398	20404	25,80 €
49	9120045474404	20405	330,00 €
48,51,53	9120045474411	20409	23,70 €
31	9120045474107	20411	7,20 €
49	9120045474251	20412	14,40 €
48	9120045474442	20414	281,00 €
51	9120045474473	20416	411,00 €
50	9120045474558	20417	535,00 €
50	9120045474565	20418	665,00 €
50	9120045474572	20419	832,00 €
50	9120045474589	20420	983,00 €
50	9120045474596	20421	1 144,00 €
51	9120045474602	20422	12,40 €
51	9120045474985	20423	17,50 €
51	9120045474626	20424	61,00 €
29,42,45	9120045474633	20427	7,10 €
29,42,45	9120045474640	20428	7,10 €
38	9120045474657	20436	64,00 €
38	9120045474664	20437	68,00 €
38	9120045474671	20438	72,00 €
38	9120045474688	20439	81,00 €
38	9120045474695	20440	96,00 €
38	9120045474701	20441	113,00 €
46,49,53	9120045474718	20442	102,00 €
49,51	9120045474725	20443	6,00 €
29	9120045474831	20455	17,50 €
29	9120045474848	20457	12,40 €
24,41,44	9120045474855	20460	29,00 €
48	9120045474879	20461	109,00 €
51	9120045474886	20462	115,00 €
24,28	9120045475081	20468	20,60 €
24,31	9120045475098	20475	23,70 €
31	9120045475104	20476	47,40 €

Page	EAN-Code	Item no.	Rec. trade price
23	9120045475180	20481	69,00 €
24	9120045475197	20483	6,80 €
24	9120045474930	20484	9,60 €
24,28	9120045474947	20485	47,40 €
25,31,42	9120045474954	20487	9,40 €
23	9120045474961	20488	141,00 €
53	9120045474978	20489	177,00 €
53	9120045474992	20490	57,00 €
52	9120045475005	20491	1 029,00 €
52	9120045475012	20492	1 272,00 €
52	9120045475029	20493	1 545,00 €
52	9120045475036	20494	1 815,00 €
52	9120045475043	20495	2 081,00 €
52	9120045475050	20496	2 394,00 €
53	9120045475067	20497	1 639,00 €
53	9120045475203	20498	58,00 €
24	9120045475241	20509	8,00 €
19	9120045475265	20522	7,10 €
19	9120045475272	20523	8,20 €
56	9120045475296	20525	340,00 €
56	9120045475302	20526	335,00 €
56	9120045475319	20527	259,00 €
23	9120045476156	20559	345,00 €
23	9120045476149	20560	300,00 €
48	9120045476194	20562	416,00 €
24	9120045476088	20606	22,10 €
24	9120045476064	20607	17,00 €
24	9120045476019	20608	29,90 €
15	9120045475678	20609	29,90 €
15	9120045476095	20610	31,90 €
34,58	9120045476118	20611	56,00 €
24,58	9120045476026	20612	56,00 €
27,58	9120045476002	20613	56,00 €
29	9120045476101	20614	24,70 €
56	9120045475838	20615	272,00 €
56	9120045475845	20616	356,00 €
56	9120045475852	20617	510,00 €
56	9120045475869	20618	595,00 €
56	9120045475876	20619	178,00 €
56	9120045475883	20620	262,00 €
56	9120045475890	20621	131,00 €
54	9120045475722	20622	143,00 €
15	9120045475661	20623	75,00 €
36	9120045475739	20624	14,40 €
36	9120045475746	20625	14,90 €
36	9120045475753	20626	15,50 €
36	9120045475760	20627	16,00 €

Page	EAN-Code	Item no.	Rec. trade price
36	9120045475784	20628	14,40 €
36	9120045475791	20629	14,90 €
36	9120045475807	20630	15,50 €
36	9120045475814	20631	16,00 €
11,12	9120045476071	20632	10,30 €
48,51	9120045476187	20646	31,90 €
54	9120045476613	20657	196,00 €
54	9120045476620	20658	162,00 €
38,56	9120045476248	20661	41,20 €
38,56	9120045476255	20662	43,30 €
38,56	9120045476262	20663	44,30 €
38,56	9120045476279	20664	48,40 €
38,56	9120045476286	20665	55,00 €
38,56	9120045476293	20666	60,00 €
38,56	9120045476309	20667	70,00 €
38,56	9120045476316	20668	82,00 €
38,56	9120045476323	20669	96,00 €
38,56	9120045476330	20670	109,00 €
54	9120045476415	20683	114,00 €
16	9120045476484	20692	519,00 €
16	9120045476491	20693	562,00 €
16	9120045476507	20694	606,00 €
11	9120045476538	20696	55,00 €
7	9120045475326	20706	34,00 €
7	9120045475333	20707	13,40 €
7,58	9120045475340	20708	56,00 €
16	9120045476644	20711	139,00 €
7	9120045476637	20714	39,10 €
7	9120045476705	20738	17,50 €
7	9120045476712	20739	40,20 €
31	9120045477184	20816	46,50 €
31	9120045477191	20817	54,60 €
31	9120045477207	20818	66,00 €
31	9120045477276	20819	36,80 €
31	9120045477269	20824	6,00 €
31	9120045477252	20825	4,20 €
31	9120045477283	20826	30,50 €
31	9120045477290	20829	4,10 €
7	9120045477337	20849	20,50 €
7	9120045477344	20850	22,70 €
7	9120045477351	20851	22,70 €
12,13	9120045477405	20881	16,00 €
33	9120045477627	20947	7,90 €
33	9120045477634	20948	8,00 €
33	9120045477641	20949	8,50 €
33	9120045477658	20950	10,90 €

Page	EAN-Code	Item no.	Rec. trade price
33	9120045477665	20951	19,90 €
33	9120045477610	20952	35,00 €
33	9120045477672	20953	43,00 €
33	9120045477689	20954	55,00 €
33	9120045477733	20955	9,50 €
33	9120045477740	20956	22,00 €
14	9120045477726	20957	148,00 €
21	9120045477962	21000	63,00 €
21	9120045477979	21001	49,00 €
21	9120045477986	21002	73,00 €
9	9120045478020	21005	41,00 €
9	9120045478037	21006	4,50 €
9	9120045478082	21008	5,40 €
29	9120045473193	30009	22,70 €
60	9120045471977	30010	14,40 €
60	9120045471984	30011	21,60 €
60	9120045471991	30012	26,80 €
60	9120045472004	30013	33,00 €
60	9120045472011	30014	40,20 €
35	9120045472028	30017	26,80 €
35	9120045472035	30018	35,00 €
35	9120045472042	30019	43,30 €
35	9120045472059	30020	52,00 €
35	9120045472066	30021	56,00 €
25	9120045472073	30027	17,10 €
25	9120045472080	30028	18,40 €
25	9120045472097	30029	22,10 €
25	9120045472103	30030	25,80 €
37	9120045472158	30039	21,60 €
37	9120045472165	30040	23,70 €
37	9120045472172	30041	36,10 €
25	9120045472189	30042	30,50 €
25	9120045472196	30043	35,30 €
33,42,45	9120045472240	30050	8,40 €
35	9120045474466	30054	19,60 €
19	9120045472301	30063	7,40 €
19	9120045472318	30064	8,90 €
42,45,49	9120045472356	30067	20,60 €
33,42,45	9120045472387	30070	6,40 €
27	9120045473841	30146	36,10 €
42,44	9120045473025	30208	4,90 €
29	9120045473124	30210	4,30 €
29	9120045473056	30236	5,50 €
28	9120045472998	30239	20,80 €
19	9120045474862	30467	4,40 €



PROMOTION DESCRIPTION

RUNPOSTICKS - Comfort package + Cable pulling loop with thread - Set of 4

1 x RUNPOSTICKS - Comfort package 19-parts

Field of application: suspended ceilings, cable ducts, hollow walls usw...

1 x Cable pulling loop with thread RTG Ø 6 mm - set of 4

Field of application: to protect pre-assembled cables incl. plugs or to protect several cables at the same time.

For more information see product videos.

€ **186,-**

plus tax

RUNPOSTICKS - Cable pulling loop - offer
RUNPOTEC Item no. 11117



PROMOTION DESCRIPTION

RP5 without meter counter - 30 m + Cable pulling loop with hook - Set of 4

1 x RP5 without meter counter - 30 m

incl. 2 x RG7 - Guiding head with swivel

1 x Cable pulling loop with hook - set of 4

Field of application: To pull pre-fabricated cables incl. plugs in a protected manner. For pipes with an inner diameter of 14 mm or more and non-guided lines.

For more information see product videos.

INSTEAD OF € 204,20

€ **175,-**

plus tax

RP5 - Cable pulling loop - offer
RUNPOTEC Item no. 11142

**RUNPOLIFTER 4500 Cable drum lifter**

The RUNPOLIFTER 4500 is a foldable cable drum lifter that is capable of lifting drums with a maximum diameter of 1600 mm and a maximum weight of 4500 kg and a max. width of 1250 mm. For more information see product videos

Scope of supply:

1 x Lifting support right, 1 x Lifting support left
1 x Drum shaft, 2 x centring cones



Lifter Sets	Shaft length	Item no.	Rec. trade price
Lifter 1150	1150 mm	10162	2688,00 €
Lifter 1350	1350 mm	10163	2730,00 €
Lifter 1600	1600 mm	10164	2771,00 €



* ID = Inner diameter

W-BOX® | Sortimo COMPATIBLE

PROMOTION -DESCRIPTION

GF3 Glass Fiber Ø 3 mm - 30 m + RC2 Inspection camera - 30 m

- 1 x GF3 - 30 m, with integrated digital meter counter - m/ft., cable pulling system, optimal for pipe ID* 9 – 45 mm
- Total breaking load 130 kg (fiberglass rod incl. kink protection)
- 1 x RC2 Inspection camera with 30 m cable
- Field of application in combination with GF3: pipe inspections over long distances up to 50 m - as of 14 mm pipe inner diameter

For more information see product videos

INSTEAD OF € 725,00

€ **659,-**

plus tax

GF3 - 30 m - RC2 - 30 m - offer
RUNPOTEC Item no. 11146



RC2



GF3



W-BOX® | Sortimo COMPATIBLE

PROMOTION-DESCRIPTION

GF4.5 Fiberglass rod Ø 4,5 mm - 50 m + RC2 Inspection camera - 50 m

- 1 x GF4.5 Fiberglass rod Ø 4,5 mm - Profi-Set - 50 m
- Field of application: optimal for pipe-Ø 30 - 80 mm
- 1 x RC2 Inspection camera with 50 m cable
- Field of application: See description above
- Including accessories, see page 18

For more information see product videos

INSTEAD OF € 923,00

€ **789,-**

plus tax

GF4.5 - 50 m - RC2 - 50 m - offer
RUNPOTEC Item no. 11140



RC2



GF4.5

Quality check

RUNPOTEC products are checked at several stages for


- Breaking load
- Material quality
- Material fatigue
- Mechanical stress
- Functional ability

A large part of the RUNPOTEC products are made of stainless steel

- High stainless steel quality
- Precise processing
- High load capacity



EXTRA STRONG, up to max. 800 kg, has the pulling power of approx. 10 people



FOR FREE

PROMOTION OFFER!

Buy **1x Capstan winch** + **1x Pulling rope** + **1x Connection swirl**, get **1x Cable pulling grip** + **1x Cable guide roller – shaft** for free!

- CW 800 E Capstan winch incl. trolley mounting rail and strap for horizontal cable pulling (230 V / 50 Hz - 0,75 KWh / 5,1 A)
- Polyester cable pulling rope incl. steel reel
- Connection swirl with swivel Ø 30 mm
- Cable pulling grip with loop, made of high quality, galvanised steel double weave

See page 54 – 56 for details

Further information is available at www.runpotec.com or in the product video



Cable guide roller
Shaft

Cable guide roller
Shaft inside edge

Cable guide roller
90 degrees - 3 R

Cable guide roller
90 degrees



Cable guide roller - chain - 3 to 6 roll links

Cable guide roller

High performance guide roller with integrated ball bearings. Heavy duty rollers made from aluminium, CDP/ powder coated frame, Roller-Ø 130 mm, max. cable-Ø 100 mm
Load capacity 4.500 kg - Item No. 10166, 10157, 10156 and 10153
Load capacity 2.500 kg - Item No. 10189



Cable guide roller	Item no.	Rec. trade price
Shaft (for insert cables into or out of shafts)	10157	82,00 €
Shaft inside edge (for shafts or stages)	10156	82,00 €
90 degrees (for shafts or stages)	10153	157,00 €
90 degrees 3R (for corners and edges)	10189	247,00 €
Chain 3-parts (universally applicable)	10166	241,00 €
Chain 4-parts (universally applicable)	10199	321,00 €
Chain 5-parts (universally applicable)	10200	402,00 €
Chain 6-parts (universally applicable)	10201	481,00 €



Irlachstrasse 31
5303 Thalgau / Austria
Phone: +43 6235 20335-0
Fax: +43 6235 20335-35

office@runpotec.com
www.runpotec.com

Newsletter
Sign up



Scan the QR code, subscribe and be informed immediately about new products and promotions.

