CHANCE®

SUPPLEMENTAL CATALOG
BULLETIN 5C-1.1
APRIL 2013

Clamps, Drop Wire Service

1-2 Pair and 6 Pair Clamps

Attaches to hooks and span clamps to secure ends (pole, building or mid-span) of 1-2 & 6 pair communication service drops



- **1-2 pair meets the requirements of Telcordia specification GR-3174**
- **Clamp Strength Rating:**
  1-2 pair clamps - 555 lbs.
  6 pair clamps - 800 lbs.

Drop clamps will exceed the rated tensile strength of the applicable cable

Features

- Available in either stainless steel or aluminum
- 1-2 pair supplied with serrated shims
- 6 pair supplied with dimpled shims



1-2 Pair Drop Wire Clamp



6 Pair Drop Wire Clamp

Material

Stainless steel clamps - 304 stainless steel
Aluminum clamps - 5052-H32 aluminum
Clamp bail wire (aluminum and stainless clamps) - 430 stainless

Catalog Number	Drop Cable	Material	Shim Style	Approx. Ship Wt. per Each
C2PRAS	1-2 Pair	Aluminum	Serrated	.08 lb.
C2PRSS		Stainless		.11 lb.
C6PRAD	6 Pair	Aluminum	Dimpled	.14 lb.
C6PRSD		Stainless		.18 lb.

Clamps, Drop Wire Service

Universal CATV Clamp

Attaches to hooks and span clamps to secure ends (pole, building or mid-span) of CATV messengered service drops



Catalog Number CMDCA
CATV Service Drop Clamp

Material

Clamp - 5052-H32 aluminum
Clamp bail wire - 430 stainless

Catalog Number	Drop Cable	Approx. Ship Wt. per Each
CMDCA	Messengered COAX	.05 lb.

NOTE: Hubbell has a policy of continuous product improvement.
We reserve the right to change design and specifications without notice.

HUBBELL®
Power Systems, Inc.

www.hubbellpowersystems.com

HUBBELL®

210 N. Allen St. • Centralia, MO 65240

©2013 Hubbell Incorporated

Printed in USA