FHD-MM1D



Fiber Optic Drop Cable Assembly, SC/APC to SC/APC, universal flat locatable/tonable

- Hardened connectors are factory-terminated and environmentally sealed for use in optical drop cable deployments
- Hardened drop cables incorporate hardened connector technology that is designed to withstand the rugged outside plant environment
- Hardened drop cables simplify installation and maintenance by reducing splicing requirements in the distribution portion of the network
- *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

OBSOLETE

Replaced By:

HCA-MM1D PRODIGY™ SC/APC w/ Short Breakout to SC/APC w/ Short Breakout, USD Toneable Cable

Product Classification

Regional Availability	Asia | Australia/New Zealand | EMEA | Latin America | North America
Product Type	Fiber drop cable assembly
Product Series	FHD
Government Requirements	Build America Buy America (BABA) compliant*
Ordering Note	Drops are automatically coiled 0 to 1,000 ft (305 m), unless spool option "L" or "R" is specified for this range of length | Drops are automatically spooled at 1,001 ft (306 m) with connector B deploying first from spool

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: April 8, 2026

General Specifications


Cable Type	Locatable - Universal Flat
Connector A, quantity	1
Color, boot A	Green
Color, connector A	Green
Connector B, quantity	1
Color, boot B	Green
Color, connector B	Green
Interface, Connector A	SC/APC with pulling sock
Interface, Connector B	SC/APC
Jacket Color	Black
Location of Manufacturing	Catawba, North Carolina
Total Fibers, quantity	1
Transmission Standards	IEC 61753-1 | IEC 61754-4 | IEC 61755

Dimensions

Breakout Length, connector A	203.2 mm | 8 in
Breakout Length, connector B	203.2 mm | 8 in
Cable Assembly Length Range (m)	1 – 750
Cable Assembly Length Range (ft)	50 – 2000
Cable Outer Diameter	4.6 x 7.4 mm (0.18 x 0.29 in)

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: April 8, 2026

Representative Image



Ordering Tree

FHD- □ □ 1 □ - □□□□□□ □

Connector A

H	Hardened Full Size
J	SC/APC****
X	DLX

Connector B

H	Hardened Full Size
J	SC/APC
X	DLX
N	SC/UPC
K	LC/UPC
V	LC/APC
0	STUB

Cable type

A	Flat Dielectric
B	Flat Locatable/ Toneable
C	Universal Flat Dielectric
D	Universal Flat Locatable/Toneable
K*	Round Dielectric

Cable length**

0050F	50 Feet
0100F	100 Feet
1000F	1000 Feet
2000F	2000 Feet

Special request***

L	Spooled: Connector 1 deploys first from spool
R	Spooled: Connector 2 deploys first from spool

* Cable Type K not available with LC & SC Options
** Cable Length shown as an example, additional cable lengths available upon request up to 2,000 ft. (600 m).
*** Special Request Feature not available with cable types K.
Drops are automatically coiled 0 to 1,000 ft. unless "L" or "R" is specified for this range of length.
Drops are automatically spooled at 1,001 ft. with Connector B deploying first from spool. Add "L" to lengths over 1,001 ft. if Connector A needs to deploy first.
**** Includes pulling sock - 25 lbs. of pulling force

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: April 8, 2026

Mechanical Specifications

Minimum Bend Radius, loaded	91.44 mm | 3.6 in
Minimum Bend Radius, unloaded	63.5 mm | 2.5 in
Tensile Load, long term, maximum	400.34 N | 90 lbf
Tensile Load, short term, maximum	1334.466 N | 300 lbf
Cable Crush Resistance, maximum	44 N/mm | 251.246 lb/in

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.657.A2, TeraSPEED®
Insertion Loss, maximum, connector A	0.4 dB
Insertion Loss, maximum, connector B	0.4 dB
Insertion Loss, typical	0.16 dB
Return Loss, minimum, connector A	65 dB
Return Loss, minimum, connector B	65 dB

Environmental Specifications

Installation temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Operating Temperature Note	Specification applicable to non-terminated bulk fiber cable
Storage Temperature	-40 °C to +75 °C (-40 °F to +167 °F)
Environmental Space	Outdoor, buried
Jacket UV Resistance	UV stabilized
Qualification Standards	NEMA type 6, 10 ft waterhead | Telcordia GR-20 | Telcordia GR-3120

Packaging and Weights

Cable weight	36 kg/km | 24.191 lb/kft
Packaging quantity	1

©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: April 8, 2026

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



©2026 CommScope Technologies LLC, an Amphenol company. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: April 8, 2026