BE12T716 Flexible Copper Braid

By Burndy
Catalog # BE12T716

Flexible Copper Braid



Features

- Most Burndy braid are UL Listed and CSA Certified
- Pressed seamless copper ferrules provide added durability and prevent fraying, providing extra strength for a robust bonding connection
- Braid is especially suited for applications that require flexibility or resistance to vibration
- Extra fine stranding gives enhanced flexibility
- Ferrules clearly marked with Burndy braid type and UL markings (where appropriate)
- Available in custom lengths and hole sizes to suit your needs (contact your local sales representative for non-standard configurations)
- For assistance in finding the perfect braid for your needs click here for our Braid Configurator Tool: www.hubbell.com/config/BRAID

Specifications

Standards - RoHS Compliance Status	CM
UL Listed	Yes
Certification - CSA Approved	Yes

Configuration

Connector Type	Braid

Dimensions

Package Height	0.000 in
Length	12 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	305 mm
Dimension - Length Overall inch	12 in

General

Product Family	Grounding and Bonding Connectors>Braid, Jumpers, Shunts>Cable Tray Bonding Jumpers
Product Type	Mechanical
UPC	621945431591
Material	Copper
UPC 12 Digit	621945431591
UPC 14 Digit GTIN	00621945431591

Logistics

Minimum Pack Quantity	1

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved