
SFG22HDX-12-B



G22HDX High Capacity Sector Frame with 2 7/8in OD x 12.5ft face. Antenna pipes sold separately.

Product Classification

Product Type	High capacity Tower sector frame
Product Series	G2

General Specifications

Application	4G LTE antenna/radio mount
Mounting	Angle 60°, 203.2 mm (8 in) | Straight or tapered legs up to 203.2 mm (8 in) OD
Patent Number	Patent pending
Pipe, quantity	0
Sectors, quantity	1
Tower Taper	Non-tapered | Tapered

Dimensions

Height	990.6 mm | 39 in
Face Width	3.81 m | 12.5 ft
Width	3,810 mm | 150 in
Face Support Pipe Diameter	73.025 mm | 2.875 in
Mounting Diameter, maximum	218.44 mm | 8.6 in
Mounting Diameter, minimum	38.1 mm | 1.5 in
Pipe Outer Diameter	73.025 mm | 2.875 in
Stand-off Distance	1,066.8 mm | 42 in

Material Specifications

Material Type	Hot dip galvanized steel

Mechanical Specifications

Wind Rating	For Specifications, please contact your local ANDREW representative
Wind Rating Test Method	TIA/EIA-222-G

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: October 6, 2026

ANDREW® an Amphenol company

SFG22HDX-12-B

Packaging and Weights

Included	Frame | Stiff arms (2) | Tower attachment
Packaging quantity	1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



* Footnotes

Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code

©2026 ANDREW, an Amphenol company. All rights reserved. Amphenol and ANDREW are registered trademarks of Amphenol and/or its affiliates in the U.S. and other countries. All product names, trademarks and registered trademarks are property of their respective owners.
Revised: October 6, 2026