

Representative

Catalog Number: **DG4X1C-1600**
Product ID: 7TAA241030R0058
UPC Number: 79120721713
Status: Active

Riser-Gard Fiber Optic Corrugated Conduit, Size 1-1/4 Inch, Outer Diameter 1.67 Inch, Inner Diameter 1.31 Inch, Wall Thickness 0.080 Inch, Length 1,600 Feet, Material PVC, Color Orange, with Pull Tape

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Carlon
Type	Riser-Gard Flexible Raceway
Special Features	UL Listed and is available with tape pre-installed.
Application	Riser-Gard is suitable for use in vertical runs in a shaft or between floors, as well as areas other than the plenum.
Standard	UL e151168
Trade Size	1-1/4 Inch
Outside Diameter	1.67 Inches
Inside Diameter	1.31 Inches
Length	1,600 ft
Material	PVC
Color	Orange

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	31.75mm
Nominal size in inch	1 1/4 inch
Outer diameter	42.4mm
Inner diameter	33.3mm
Material	PVC
Operating temperature	-20 - +40°C
UV resistant	N
Colour	Orange
Sheathing material	Not sheathed
Approved according to DIN EN 61386-23	N
Approved according to UR	N
Approved according to LUL/British Standard	N
Approved according to Lloyd's Register TA	N
Approved according to UTAC	N
Approved according to DIN 5510	N
Approved according to NF F 16-101	N

Packaging

Outer Quantity	1600
Outer Dimensions (inches)	48x45x23
Weight Uom	21.63 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-AC04182
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com